

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	5. LEASE DESIGNATION AND SERIAL NO. 078204-A
2. NAME OF OPERATOR Mesa Petroleum Co.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 1660 Lincoln St., Suite 2800, Denver, Colorado 80264	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 950' FNL & 1550' FEL	8. FARM OR LEASE NAME Trieb Federal
14. PERMIT NO.	9. WELL NO. 2E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6107 GR	10. FIELD AND POOL, OR WILDCAT Blanco MV - Basin Dakota
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33-T30N-R10W
	12. COUNTY OR PARISH San Juan
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) Spud & test BOP <input checked="" type="checkbox"/>	
(Other) <input type="checkbox"/>		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above well was spudded May 3, 1980 at 4:00 P.M. A 15" hole was drilled to 248' KB. New 10 3/4" 40 1/2"/ft K-55 STC casing was set at 241' KB and cemented with 250 sxs Class "B" 2% CaCl. Circulated cement to the surface. Plug down at 11:00 P.M. May 3, 1980.

NUBOPD and tested to 800 psi for 30 minutes - OK. Drilled out from under surface casing with 8 3/4" bit.

xc: J. Archer, J. Alexander, T. L. Slife, Centrl Rec., Div



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Div. Drilling Supervisor

DATE 5/5/80

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
DATE

NMOCC

MAY 16 1980

*See Instructions on Reverse Side

BY E. J. Boehr
FARMINGTON DISTRICT