STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION



This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST COMO DIV.

Operator CONOCO INC			С	Lease	BRUINGTON DISTINGUE 15E (MD)			
Location of Well:	Unit	Sec. 15	Twp30	Rge	11	Cour	SAN JUAN	
NAME OF RESERVOIR OR POOL			TYPE OF P (Oil or G		METHOD OF PROD. (Flow or Art. Lift)	PROD. MEDIUM (Tbg. or Cag.)		
Upper Completion				GAS	GAS FLOW		TBG.	
Lower Completion DAKOTA			GAS	FLOW		TBG.		
			PRE-FLO	OW SHUT-IN P	RESSURE DAT	ΓA		
Upper	1	Hour, date shut-in Langth of time shut-in			Si press. psig 400		Stabilized? (Yes or No)	
Completion 0		7-31-94		4-Days			NO	
Lower Completion	Hour, date si	7-31-94	Length of time shu		Si press. psig 665		Stabilized? (Yes or No) NO	
				FLOW TEST	NO. 1			
Conmenced	at (hour, dat	o) *	08-04-94		Zone producing (Upper or Lower): LOWE?			
TIME (hour, date)		LAPSED TIME SINCE*	PRES Upper Completion	SURE Lower Completion	PROD. ZONE TEMP.		REMARKS	
08-0	2-94	1-Day	390	650		вотн 2	ZONES SHUT-IN	
08-0	3-94	2-Days	395	660		вотн 2	ZONES SHUT-IN	
08-0	4-94	3-Days	400	665		вотн 7	ZONES SHUT-IN	
08-0	5-94	1-Day	410	160		LOWER	ZONE FLOWING	
08-06-94		2_Days	410	156		LOWER	ZONE FLOWING	
Producti	on rate di	uring test		•	7			
Oil:		ВОР	D based on	Bbls. in	Но	urs G	Grav GOR	
Gas:			MCF	PD; Tested thru	(Orifice or Me	eter):		
		•		EST SHUT-IN P	RESSURE DAT	Ĩ A		
Upper Compietion			ıt-in	Si press. paig		Stabilized? (Yes or No)		
Lower Hour, date shut-in		Length of time shu	Length of time shut-in			Stabilized? (Yes or No)		

REMARKS

FLOW TEST NO. 2

PRESSURE

icing (Upper or Lower):

PROD. ZONE

(updit pera)	-	Oppor Comprosion			
			 		
		Ì			
	 				
			}		ļ
	•				*
Production rate d	_				_
Oil:	ВОР	D based on	Bbls. in	Hours	Grav GOR
					_
Gas:		MCI	PD: Tested thru	(Orifice of Meter	r):
D o alon.					
Remarks:					
I hereby certify the	hat the informati	ion herein contair	ned is true and co	omplete to the be	st of my knowledge.
Approved			10 (OperatorC	ONOCO INC
Approved	il Conservation	Division		Operator	DANIDHILLIDO
	Johnny Role		1	Ву	DAN PHILLIPS
ļ	7				DUCTION SPECIALIS
By	JAN 111	1005		Title III	MOLION OF ECIALION
Title	ANN TI	ון מצפו		Date	CONOCO, INC.
	EDITION OF STA		•		
101	EPUTY OIL & GAS	INSPECTORI			

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

d at (hour, date) **

TIME

LAPSED TIME

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).