## Form 9-331 Form Approved. Dec. 1973 Budget Bureau No. 42-R1424 **UNITED STATES** 5. LEASE DEPARTMENT OF THE INTERIOR SF-079511-A **GEOLOGICAL SURVEY** 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME SUNDRY NOTICES AND REPORTS ON WELLS ្ កញ្ញា (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) 8. FARM OR LEASE NAME ន្តដ្ Gartner name 5 1. oil gas well $\mathbf{X}$ well other 9. WELL NO. 2. NAME OF OPERATOR Tenneco Oil Company 10. FIELD OR WILDCAT NAME Basin Dakota/Blanco Pictured Clif-3. ADDRESS OF OPERATOR <u>720 S. Colo. Blvd., Denver, CO 80222</u> 11. SEC., T., R., M., OR BLK. AND SURVEY OR 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 7833 below.) Sec. 29: T30N; R8W 1030'FSL, 1040'FEL, Unit P AT SURFACE: 12. COUNTY OR PARISH 13. STATE AT TOP PROD. INTERVAL: San Juan A Bal New Mexico AT TOTAL DEPTH: 14. API NO. 무료결혼 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6183'GR - 赤瓜ゟな REQUEST FOR APPROVAL TO: SUBSECUENT REPORT OF: tounes: TEST WATER SHUT-OFF FRACTURE TREAT , 40. γαει γαγ SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone PULL OR ALTER CASING change on Form 9-330.) obtained Hew plant in the state of the state MULTIPLE COMPLETE CHANGE ZONES tane t ABANDON\* (other) Report on Drilling Operations 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Spudded 124" @ 12:00PM, 3/12/80. RU & ran 206' of 9 5/8" 36# csg & set @ 221'. Cmt. w/225 sxs CLB, w/3% CACL2. Circ. to surface. Reduced hole to 8 3/4"& drilled to 3460' where 3468' of 7", 23# csg was set. Cmt w/600 sxs 50/50 Pozmix, tailed w/150 sxs CL B w/2% CACL2. Lost circulation. Ran temp. survey & determined TOC @ 1600'. Reduced hole to 64" & drilled to TD of 7500' on 3721/80. RU & ran 544' of 11.6# & 3648' of 10.5 #, 4 1/2" csg. w/liner and set @ 7485'. TOL: 3311'. Cmt w/425 sxs 50/50 Pozmix w/4% gel & .1% TIC (c) Let w/100 sxs CLB neat. Circ to top of liner. Released rig 3/21/80. WOCU 969 Subsurface Safety Valve: Manu, and Type 18. I hereby cortify that the foregoing is true and correct TITLE Admin. Supervisor DATE (This space for Federal or State office use) APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side