

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR  
SUN OIL COMPANY

3. ADDRESS OF OPERATOR

2525 N.W. Expressway, Okla. City, OK 73112

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1110' FNL & 850" FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Drill ☒

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☒

RECEIVED

SEP 11 1980

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE - Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-30-80 - Loaded hole w/10 bbls 2% KCL water. GIH w/Baker Mod "R" PKR on 2-3/8" tbg. set pkr @ 6,625'. Ru to swab. well kicked off.

8-31-80 - So by RBP @ 6,665' - 6554'. Unseated pkr. Pooh. Ru GO. Perf. 4-1/2" CSG 6,636' - 42', 6,600 - 20', 6,548' - 54' w/3-3/8 densi gun. Rd GO. GIH w/4-1/2" Baker Mod "B" RBP, Mod "R" PKR on 2-3/8" Tbg. set RBP @ 6,665'. set PKR @ 6,573'.

9-1-80 - SDFS

9-2-80 - SDFS

9-3-80 - RU Dowell. ACDZ down TBG w/2,000 gals. 15% HCL. REL PKR & GIH. Tagged RBP @ 6,665'. Circ sand. PU to 6,570'. & Attempted to reset RBP POOH- Left RBP in hole. GIH w/Ret. head tagged RBP @ 6,740'.

9-4-80 - PU 4-1/2" BAKER MOD "B" RBP & MOD "R" PKR & GIH. RBP SET @ 3,690' ON WAY IN/ UNSET RBP & GIH TO 6,575'/ ATTEMPT TO SET RBP/ GIH TO 6,720'/ cont-

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft. inued

18. I hereby certify that the foregoing is true and correct

SIGNED Jeannie Owens TITLE Prod. Staff Assoc. DATE \_\_\_\_\_

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF FARMINGTON DISTRICT

SEP 15 1980

NMOCG

\*See Instructions on Reverse Side

BY BW FARMINGTON DISTRICT



PU FALLEN RBP/ POOH TO 6,577'/ ATTEMPT TO SET RBP/ PU TO 6,575' &  
SET RBP/ PU & SET PKR @ 6,565'/ PU & SET PKR @ 6,503'/ DOWELL  
ACIDIZED DOWN TBG WITH 500 GAL 15% HCL. REL PKR & GIH/ WASHED SAND & BALLS  
OFF RBP/ LATCHED ONTO RBP & GIH TO 6,665'/ ATTEMPT TO SET RBP/ GIH  
TO 6,720'/ PU FALLEN RBP/ PU TO 6,665' & SET RBP/ PU & SET PKR @ 6,650'/  
PU TO 6,503' & SET PKR/ NU TREE/

9-5-80 - BIT #18 - 6-3/4", WORKED TIGHT CONN POOH TO CHECK BHA

