5. LEASE NM 047 ı

UNITED STATES						
DEPARTMENT	OF	THE	INTERIOR			
GEOLOGI	CAL	SUR	RVEY			

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	N/A 7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	N/A
1 oil goo	8. FARM OR LEASE NAME New Mexico Federal -N-
1. oil gas well other	9. WELL NO.
2. NAME OF OPERATOR	1 E
SUN OIL COMPANY	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota
2525 N.W. Expressway, Okla. City, OK 73112	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	SE SE Sec. 17-T30N-R12W
AT SURFACE: 1120' FSL & 1120' FEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
HEI ONT, ON OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5812' GR
TEST WATER SHUT-OFF	
RACTURE TREAT	(NOTE: Report results of inumble completion of one change on Form 4-330.)
GHOOT OR ACIDIZE REPAIR WELL T	Carolina Contraction
PULL OR ALTER CASING \	(NOTE: Report results of invitable completion of come
MULTIPLE COMPLETE	Dies Con.
CHANGE ZONES	DIST. 30M.
ABANDON*	
Other) Drill X	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent 7-19-80 - Drld to 3,321' w/Bit #3-7-7/8" 7-20-80 - Drld to 3,875' w/Bit #3-7-7/8" 7-21-80 - Drld to 4,100' w/Bit #3-7-7/8". Tridown from 4,040'-4,100'. Drld to 4,7-22-80 - Drld to 4,655' w/Bit #4-7-7/8". 7-23-80 - Drld to 5,036' w/Bit #4-7-7/8". 7-24-80 - Drld to 5,410' w/Bit #4-7-7/8".	rectionally drilled, give subsurface locations and to this work.)* ipped for new Bit. Washed
, 2, 35 2, 10 3, 110 4, 5, 7, 7, 8	
•	Four 1 188,
	- S. GECTOMORE CONVEY FARROAG OR CONE
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED CARNE CLUENS TITLE Prod. Staff Ass	OC. IDATE 7-30-80
(This space for Federal or State offic	e use)
APPROVACCEPTED FOR RECORD TITLE	DATE
AUG 05 1980	

*See Instructions on Reverse Side

		7
- 1		