UNITED STATES

SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS TO most use this form for proposals to delife to despens or plug back to a different carried to the proposals of delifer to despens or plug back to a different carried to the proposals of delifer to despens or plug back to a different carried to the proposals of delifer to despens or plug back to a different carried to the proposals of delifer to despens or plug back to a different carried to the proposals of delifer to a different carried to the proposals of deliferation of the proposals of the proposals of deliferation of the proposals of the proposals of deliferation of the proposals of	REMINESTED AF SHE INCOME.	J. LEASE
SUNDRY NOTICES AND REPORTS ON WELLS (Co not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use form 9-331-2 for such proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use form 9-331-2 for such proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use form 9-331-2 for such proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use form 9-331-2 for such proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use from 9-331-2 for such proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.) (Do not use this form for proposals.) (Do not use this for	DEPARTMENT OF THE INTERIOR	NM 047
SUNDRY NOTICES AND REPORTS ON WELLS Con not use this form for proposable to diffuse to deepen or plug back to a different exercent, use from 53-12-for yearpopeasable to diffuse to deepen or plug back to a different exercent, use from 53-12-for yearpopeasable to diffuse to deepen or plug back to a different exercent, use from 53-12-for yearpopeasable to diffuse to deepen or plug back to a different exercit, use from 53-12-for yearpopeasable to diffuse the year of year of year of the year of year o	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS Con not use this form for proposable to difful outs deepen or plug back to a different desired, the few proposable of proposable to difful outs deepen or plug back to a different service, the few proposable to difful outs deepen or plug back to a different service, the few proposable of the proposable to difful outs deepen or plug back to a different service, the few proposable of the p		N/A
NA S. FARM OR LEASE NAME	SUNDRY NOTICES AND REPORTS ON WELLS	
1. oil		N/A
2. NAME OF OPERATOR SUN OTIL COMPANY 3. ADDRESS OF OPERATOR \$10. FIELD OR WILDCAT NAME \$2525 N.W. Expressway, Okla. City, OK 73112 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 1000 'FNL & 1120 'FWL AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: REST WATER SHUT-OFF CHANGE ZONES ABANDON'* (other) Drill 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and giv proposed work. If well is directionally drilled, give subsurface locations and true vertical depths for all markers and zones pertinent to this work.)* 8-16-80 - Drild to 6339' W/Bit #5-7-7/8". 8-18-80 - Drild to 6652' w/Bit #4-7-7/8". 8-19-80 - Drild to 6652' w/Bit #5-7-7/8". 8-20-80 - Drild to 6652' w/Bit #5-7-7/8". 8-20-80 - Drild to 6652' w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD. DC & D. PRan 170 Jts of 4-1/2", 9.5# CC S 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ SX Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. APPROVED BY TILLE 2. NAMELINO. 3. ELEVATION OR BLK. AND SURVEY AREA 3. FILL BASIN DAKA. AND SURVEY AREA 3. FILL BASIN DAKA. AND SURVEY AREA 3. FILL BASIN DAKA. AND SURVEY. 3. FILL DAKA. AND SURVEY. 3.	reservoir. Use Form 9-331-C for such proposals.)	
2. NAME OF OPERATOR SUN OIL COMPANY 3. ADDRESS OF OPERATOR 2525 N.W. Expressway, Okla, City, OK 73112 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below) AT SURFACE: 1000 'FNL & 1120 'FWL AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 17. TEST WATER SHUT-OFF CHANGE ZONES BARANDON' 18. TIPE OF DEFTAL OR OF THE PORT OF: 19. WELLINO. 38. 10. Bakota AREA Sec. 18. T30N-R12W 10. COUNTY OR PARISH 13. STATE San Juan New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT OF: 18. TREAT WHITH DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and giv proposed work. If well is directionally drilled, give subsurface locations of an amarkers and zones pertinent to this work.) 8. 10. FIELD OR WILLDCAT NAME Basin Dakota AREA Sec. 18. T30N-R12W 10. COUNTY OR PARISH 13. STATE San Juan New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR 16. GR CNOTE Report results of multiple completion or x of the property of the principle of the princ	1. oil — gas on	New Mexico Federal -N-
SUN OIL COMPANY 3. ADDRESS OF OPERATOR 2525 N. M. EXPRESSMAY, OKIA, City, OK 73112 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below) AT SURFACE: 1000 'FNL & 1120 'FWL AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 17. TREAT WATER SHUT-OFF 18. CIDY OF PARISH 19. COUNTY OR PARISH 13. STATE San Juan New Mexico 14. API NO. 19. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 13. STATE 14. API NO. 19. COUNTY OR PARISH 14. API NO. 1	well Well Wolfer	
3. ADDRESS OF OPERATOR 2525 N.W. Expressway, Okla. City, OK 73112 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below), AT SURFACE: 1000 FNL & 1120 FWL AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETE OPERATIONS (Clearly state all pertinent details, and give perfection of this work.) 18. ELEVATIONS (SHOW DF, KDB, AND W FASMINGTON, N) 19. SUBSEQUENT REPORT OF: 19. COUNTY OR PARISH: 11. SEC., T.R. M., OR BLK. AND SURVEY. 19. COUNTY OR PARISH: 11. SEC., T.R. M., OR BLK. AND SURVEY. 11. SEC. 18. T30N-R12W 11. SEC. 18. T30N	2. NAME OF OPERATOR	3F
3. ADDRESS OF OPERATOR 2525 N.W. Expressway, Okla. City, OK 73112 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1000' FNL & 1120' FWL AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 16. CHECK APPROVAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and giv' per including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and giv' per including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and giv' per including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and giv' per including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are all to the period of the peri	SUN OIL COMPANY	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1000' FNL & 1120' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give perfamily including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and structural depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give perfamily including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are considered and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give perfamily locations are considered and true vertical depths for all markers and zones pertinent to this work.)* 18. 18-80 - Drild to 6612' w/Bit #5-7-7/8". 19. 8-18-80 - Drild to 66339' w/Bit #5-7-7/8". 19. 8-19-80 - Drild to 6652' w/Bit #5-7-7/8". 20. 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-19-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-10-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-10-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20. 8-10-80 - Drild to 6850' TD w/Bit #5-7-7/8". 20		-
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1000' FNL & 1120' FWL AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, WELL (SHOW DF, KDB, AND W. 5956' GR. 17. ESCRIBE PROPOSED OR COMPLETED OF STATIONS (Clearly state all portinent details, and give perfect of the pe	2525 N.W. Expressway, Okla. City, OK 73112	11. SEC., T., R., M., OR BLK. AND SURVEY OR
AT SURFACE: 1000 FNL & 1120 FWL AT TOP PROD. INTERVAL: AT TOP ADDITIONAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND W 5956 GR REPAIR WELL PULL OR ALTER CASING W. G. Charles of Form 9-330.) MULTIPLE COMPLETE W. S. GEOLOCICAL SURVEY FARMINGTON, N. S. (Short Tresults of multiple completion or zero providing estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.) OIL CON. 8-17-80 - Drld to 6013 ' W/Bit #5-7-7/8". 8-18-80 - Drld to 6339 ' W/Bit #5-7-7/8". 8-20-80 - Drld to 6652 ' W/Bit #5-7-7/8". 8-20-80 - Drld to 6655 ' W/Bit #5-7-7/8". 8-20-80 - Drld to 6650 ' TD W/Bit #5-7-7/8". 8-20-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in W/ SX Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. APPROVED BY TITLE PROD Staff Assoc I DATE 112. COUNTY OR PARISH 13. STATE SAN Juan 14. API NO. 12. COUNTY OR PARISH 13. STATE SAN Juan 14. API NO. 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR NOW MEXICO (NOTE: Report results of multiple completion or zero freed to the pool of	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	
AT SURFACE: 1000' FNL & 1120' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND W 5956' GR 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give perform 9-330.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give subsurface locations of multiple completion or zo change and true vertical depths for all markers and zones pertinent to this work.)* 18. 10. 20. 20. 20. 20. 20. 20. 20. 20. 20. 2		Sec. 18-T30N-R12W
AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETE OPERATIONS (Clearly state all pertinent details, and give perfigure pincluding estimated date of starting any proposed work. If well is directionally drilled, give subsurface location measured and true vertical depths for all markers and zones pertinent to this work.) 18. 11-80 - Dr1d to 6033' w/Bit #5-7-7/8". 18-19-80 - Dr1d to 6652' w/Bit #5-7-7/8". 18-20-80 - Dr1d to 6652' w/Bit #5-7-7/8". 18-20-80 - Dr1d to 6652' w/Bit #5-7-7/8". 18-20-80 - Dr1d to 6850' TD w/Bit #5-7-7/8". 18-20-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. 10. Subsurface Safety Valve: Manu. and Type 11. APPROVED BY 12. APPROVED BY 13. APPROVED BY 14. APPROVED BY 15. ELEVATIONS (SHOW DF, KDB, AND DF, EACH DIVERSION OF SCALE APPROVED BY 15. ELEVATIONS (SHO		
AT TOTAL DEPTRIS 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 17. CHECK APPROVAL TO: 18. SUBSEQUENT REPORT OF: 18. SUBSEQUENT REPORT OF: 19. SUBSEQUENT REPORT OF: 10. SUBSEQUENT		San Juan New Mexico
REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Drill 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give perfugences) Repair (and the vertical depths for all markers and zones pertinent to this work.)* 8-16-80 - Drild to 5612' w/Bit #4-7-7/8". 8-17-80 - Drild to 6313' w/Bit #5-7-7/8". 8-19-80 - Drild to 6329' w/Bit #5-7-7/8". 8-19-80 - Drild to 6652' w/Bit #5-7-7/8". 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 8-20-80 - CIRC & Cond hole. POOH LD. DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. CANADA TITLE PATE (This space for Federal or State office use)	AT TOTAL DEPTH:	
SUBSEQUENT REPORT OF: Subsequent report of: Subsequent report of: Subsequent report of: Subsequent report of: Subsequent report of: Subsequent report of: Subsequent report of: RECEIVED Report results of multiple completion or zero. Report results of multiple co	·	·
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT SUBJECT AUG 2 1080 SUBSEQUENT REPORT OF: SUBSEQUENT REPORT SUBJECT AUG 2 1080 SUBSURS SUBSURS SUBJECT SUBSEQUENT REPORT SUBJECT AUG 2 1080 SUBSURS SUBSURS SUBSURS SUBSURS SUBSURS OF FORM 9-330.) SUBSURS SUBSURS SUBSURS SUBSURS SUBSURS OF FORM 9-330.) SUBSURS SUBSURS SUBSURS SUBSURS SUBSURS SUBSURS OF FORM 9-330.) SUBSURS	REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF. KDB. AND WD)
RECEIVED REACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE COMPLETE COMPLETE COMPLET COMPLET COMPLET COMPLET COMPLET COMPLETE OF PRACTURE TREAT AUG 2" 1980		
RECEIVED REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE COHANGE ZONES ABANDON* (other) Drill 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent are including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)* 8-16-80 - Drild to 5612' w/Bit #4-7-7/8". 8-17-80 - Drild to 66339' w/Bit #5-7-7/8". 8-18-80 - Drild to 6639' w/Bit #5-7-7/8". 8-19-80 - Drild to 6652' w/Bit #5-7-7/8". 8-20-80 - Drild to 6850' TD w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type (This space for Federal or State office use)	<u> </u>	
SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Drill 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give perfuger and including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 8-16-80 - Drld to 5612' w/Bit #4-7-7/8". 8-17-80 - Drld to 6612' w/Bit #5-7-7/8". 8-18-80 - Drld to 6633' w/Bit #5-7-7/8". 8-20-80 - Drld to 6652' w/Bit #5-7-7/8". 8-20-80 - Drld to 6652' w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CC 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED APPROVED BY TITLE Prod Staff Assoc I DATE AUC 2. 1980 (Charge on Form 9-330.) (Clearly state all pertinent details, and give perfuger of Form 9-330.) U. S. GEQLCCICAL SURVEY Charge on Form 9-330.) Clearly state all pertinent details, and give perfuger on Form 9-330.) (Clearly state all pertinent details, and give perfuger on Form 9-330.) (Clearly state all pertinent details, and give perfuger on Form 9-330.) (Clearly state all pertinent details, and give perfuger on Form 9-330.) (Clearly state all pertinent details, and give perfuger on Form 9-330.) (Clearly state all pertinent details, and give perfuger of Form 9-300. (Con. Distance of Form 9-300. (Con. Dist		
PREPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Drill 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give perfugace including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations measured and true vertical depths for all markers and zones pertinent to this work.)* 8-16-80 - Drild to 5612' w/Bit #4-7-7/8". 8-17-80 - Drild to 6613' w/Bit #5-7-7/8". 8-18-80 - Drild to 6339' w/Bit #5-7-7/8". 8-20-80 - Drild to 6652' w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type	SHOOT OR ACIDIZE H KECEN	/FD
PULL OR ALTER CASING MULTIPLE COMPLETE MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Drill 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give perform an including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)* 8-16-80 - Drld to 5612' w/Bit #4-7-7/8". 8-17-80 - Drld to 6339' w/Bit #5-7-7/8". 8-19-80 - Drld to 6652' w/Bit #5-7-7/8". 8-20-80 - Drld to 6850' TD w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type		
CHANGE ZONES ABANDON* (other) Drill 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give perform an including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location are measured and true vertical depths for all markers and zones pertinent to this work.)* 8-16-80 - Drld to 5612' w/Bit #4-7-7/8". 8-17-80 - Drld to 6013' w/Bit #5-7-7/8". 8-18-80 - Drld to 6339' w/Bit #5-7-7/8". 8-20-80 - Drld to 6652' w/Bit #5-7-7/8". 8-20-80 - Drld to 6850' TD w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type	PULL OR ALTER CASING THE ALIG 9"	(NOTE: Report results of multiple completion or zone
(other) Drill The proposed or completed operations (Clearly state all pertinent details, and give performance including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location as measured and true vertical depths for all markers and zones pertinent to this work.)* 8-16-80 - Drld to 5612' w/Bit #4-7-7/8". 8-17-80 - Drld to 6013' w/Bit #5-7-7/8". 8-18-80 - Drld to 6339' w/Bit #5-7-7/8". 8-19-80 - Drld to 6652' w/Bit #5-7-7/8". 8-20-80 - Drld to 6652' w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type	MULTIPLE COMPLETE	1000
(other) Drill X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give performance including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location as measured and true vertical depths for all markers and zones pertinent to this work.)* 8-16-80 - Drld to 5612' w/Bit #4-7-7/8". 8-17-80 - Drld to 6013' w/Bit #5-7-7/8". 8-18-80 - Drld to 6339' w/Bit #5-7-7/8". 8-19-80 - Drld to 6652' w/Bit #5-7-7/8". 8-20-80 - Drld to 6652' w/Bit #5-7-7/8". 8-20-80 - Drld to 6850' TD w/Bit #5-7-7/8". Made 20 std short Trip. CIRC. 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ SX Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type Set @	CHANGE ZONES U. S. GEOLOGICAL	SUBJECT
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location as measured and true vertical depths for all markers and zones pertinent to this work.)* 8-16-80 - Dr1d to 5612' w/Bit #4-7-7/8". 8-17-80 - Dr1d to 6013' w/Bit #5-7-7/8". 8-18-80 - Dr1d to 6339' w/Bit #5-7-7/8". 8-19-80 - Dr1d to 6652' w/Bit #5-7-7/8". 8-20-80 - Dr1d to 6652' w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. P00H LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CC 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type		N. I.S
8-16-80 - Dr1d to 5612' w/Bit #4-7-7/8". 8-17-80 - Dr1d to 6013' w/Bit #5-7-7/8". 8-18-80 - Dr1d to 6339' w/Bit #5-7-7/8". 8-19-80 - Dr1d to 6652' w/Bit #5-7-7/8". 8-20-80 - Dr1d to 6650' TD w/Bit #5-7-7/8". 8-20-80 - Dr1d to 6850' TD w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type	(otner) Drill	
8-16-80 - Dr1d to 5612' w/Bit #4-7-7/8". 8-17-80 - Dr1d to 6013' w/Bit #5-7-7/8". 8-18-80 - Dr1d to 6339' w/Bit #5-7-7/8". 8-19-80 - Dr1d to 6652' w/Bit #5-7-7/8". 8-20-80 - Dr1d to 6652' w/Bit #5-7-7/8". 8-20-80 - Dr1d to 6650' TD w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type	17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	e all pertinent details and give pertinent dates
8-16-80 - Dr1d to 5612' w/Bit #4-7-7/8". 8-17-80 - Dr1d to 6013' w/Bit #5-7-7/8". 8-18-80 - Dr1d to 6339' w/Bit #5-7-7/8". 8-19-80 - Dr1d to 6652' w/Bit #5-7-7/8". 8-20-80 - Dr1d to 6650' TD w/Bit #5-7-7/8". 8-20-80 - Dr1d to 6850' TD w/Bit #5-7-7/8". 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type	including estimated date of starting any proposed work. If well is d	irectionally drilled, give subsurface locations and
8-1/-80 - Drld to 6013' w/Bit #5-7-7/8". 8-18-80 - Drld to 6339' w/Bit #5-7-7/8". 8-19-80 - Drld to 6652' w/Bit #5-7-7/8". 8-20-80 - Drld to 6850' TD w/Bit #5-7-7/8". Made 20 std short Trip. CIRC. 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type Set @	measured and trac vertical depths for an markers and zones pertiner	it to this work.)*
8-18-80 - Drld to 6339' w/Bit #5-7-7/8". 8-19-80 - Drld to 6652' w/Bit #5-7-7/8". 8-20-80 - Drld to 6850' TD w/Bit #5-7-7/8". Made 20 std short Trip. CIRC. 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CC 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type Set @		Diez CO
8-19-80 - Drld to 6652' w/Bit #5-7-7/8". 8-20-80 - Drld to 6850' TD w/Bit #5-7-7/8". Made 20 std short Trip. CIRC. 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
8-20-80 - Drld to 6850' TD w/Bit #5-7-7/8". Made 20 std short Trip. CIRC. 8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type Set @	·	
8-21-80 - Schlumberger ran DIL - 6849-364' & CNL-FDC-GR-CAL 6848-5582', 4,8 3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type		
3,612' & 2,350-1,700'. Now TIH w/Bit. 8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/ sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type Set @	8-20-80 - Drid to 6850 ' TD w/Bit $#5-/-//8$ ". N	Made 20 std short Trip. CIRC.
8-22-80 - CIRC & Cond hole. POOH LD.DC & D.PRan 170 Jts of 4-1/2", 9.5# CCS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type Set @	8-21-80 - Schlumberger ran DIL - 6849-364' &	CNL-FDC-GR-CAL 6848-5582', 4,840-
CS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type		
CS 6,948'. FC 6,907'. CIRC cmt w/915 SX Howco light. Tailed in w/sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type	8-22-80 - CIRC & Cond hole. POOH LD.DC & D.P.	Ran 170 Jts of 4-1/2", 9.5# CSG.
sx Class A. Dropped plug. started displacement. Pumped 10 Bbls - press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type	CS 6,948'. FC 6,907'. CIRC cmt w/9	15 SX Howco light. Tailed in w/100
press increased to 2,000#. TOC inside 4-1/2" CSG 800'. Bled press ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type	sx Class A. Dropped plug. started of	displacement. Pumped 10 Bbls -
ND BOP. Set slips & cut off csg. Subsurface Safety Valve: Manu. and Type	press increased to 2,000#. TOC ins	ide 4-1/2" CSG 800'. Bled press of
Subsurface Safety Valve: Manu. and Type		, — от поставания работ с
18. I hereby certify that the foregoing is true and correct SIGNED Cannie Curn TITLE Prod Staff ASSOC I DATE (This space for Federal or State office use) APPROVED BY DATE		•
18. I hereby certify that the foregoing is true and correct SIGNED Cannie Curn TITLE Prod Staff ASSOC I DATE (This space for Federal or State office use) APPROVED BY DATE	0.1. (0.6) Velocitics 17	
SIGNED Cannie Cwent TITLE Prod Staff ASSOC I DATE (This space for Federal or State office use) APPROVED BY DATE	Subsurface Safety valve: Manu. and Type	Set @ Ft.
SIGNED Cannie Cwent TITLE Prod Staff ASSOC I DATE (This space for Federal or State office use) APPROVED BY DATE	18. I hereby certify that the foregoing is true and correct	
(This space for Federal or State office use) APPROVED BY DATE		•
(This space for Federal or State office use) APPROVED BY DATE	SIGNED Jeannie Wens TITLE Prod Staff Ass	SOC_I DATE
APPROVED BY DATE		
APPROVED BY DATEDATE		
CONDITIONS OF APPROVAL, IF ANY:	APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE

ACCEPTED FOR RECORD

AUG 28 1980

*See Instructions on Reverse Side

•