

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
501 Airport Drive, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 950 FNL x 820 FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Completion <input type="checkbox"/>	

5. LEASE
SF - 078139
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Elliott Gas Com N
9. WELL NO.
1E
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NE/4, NE/4, Section 33
T30N, R9W
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
30-045-24382
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5766' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 10-3-80. Total depth of the well is 7090', and plug back depth is 7010'. Perforated intervals from 6923' to 6952', with 2 spf, a total of 58, .38" holes. Perforated intervals from 6812' to 6838' with 2 spf, a total of 52, .38" holes. Sand water fraced with 83,000 gal of frac fluid and 299,000# 20-40 sand. Landed 2 3/8" tubing at 6969'. Swabbed the well and released the rig on 10-14-80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____

18. I hereby certify that the foregoing is true and correct

SIGNED E. E. SYCORA TITLE Dist. Admin. Supvr DATE 11-12-80

(This space for Federal or State office use)

APPROVED BY **ACCEPTED FOR RECORD**

CONDITIONS OF APPROVAL, IF ANY:

NOV 19 1980

FARMINGTON DISTRICT

BY BL

NMOCC

*See Instructions on Reverse Side

