UNITED STATES DEPARTMENT OF THE INTERIOR

5. LEASE	
SF-078139	
6. IF INDIAN, ALLOT	TEE OR TRIBE NAME
7. UNIT AGREEMENT	NAME

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
4	Elliott Gas Com R
1. oil gas well other	9. WELL NO.
2. NAME OF OPERATOR	1E = 3 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
AMOCO PRODUCTION COMPANY	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota
501 Airport Drive, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NE/4 NW/4, Section 34
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA NE/4.NW/4, Section 34 T30N, R9W A ALB 3
below.) AT SURFACE: 800 FNL × 1630 FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same	San Juan
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	30-045-24383
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5761 GL 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL REPAIR WELL Change on Form 9-330.) MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Completion 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Completion operations commenced on II-21-80. Total depth of the well is 7133', and plug back depth is 7050'. Cored interval 2319-2335 and 2370 - 2390 and 2442-2458. Recover total 52' of core. Perforated intervals from 6818' to	
6847, and 6932 'to 6954 ', with 2 spf, a total with 74,868 gal of frac fluid and 154,340 $#$ 2 at 6965 '. Swabbed the well and released the	of 102, .38" holes. Sand water fraced 20-40 sand. Landed 2 3/8" tubing
Subsurface Safety Valve: Manu. and Type	Set @ O/LFt/g
18. I hereby certify that the foregoing is true and correct	
Odgina Japan . Dist. Admin.	Supvr. 1-6-80 3

SIGNED _____E. E. SYOBODA (This space for Federal or State office use) APPROVED BY . ACCEPTED FOR RECURD

JAN 1 2 1981

*See Instructions on Reverse Side