

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-10870

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator TEXACO Inc. Attention: G. L. Eaton	8. Farm or Lease Name New Mexico Com. "C"
3. Address of Operator P. O. Box 2100, Denver, Colorado 80201	9. Well No. 1A
4. Location of Well UNIT LETTER D , 790 FEET FROM THE North LINE AND 840 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 30N RANGE 10W NMPM.	10. Field and Pool, or Wildcat Blanco Mesaverde
15. Elevation (Show whether DF, RT, GR, etc.) 5975' GR	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER <u>Ran Surface Casing</u> <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded at 7:00 AM, 9-15-80.

Ran 260' (7 joints) of 9-5/8" OD 32# K-55 ST&C Casing. Landed at 260' KB.
Cemented with 175 sacks Class "B", 2% CaCl₂ and 1/4# flo-seal cement
returned to surface. Plug down, did not bump, at 6:00 PM, 9-15-80. Float
held.

Casing tested at 1100 psi for 30 minutes. Held ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED G. L. EATON TITLE District Superintendent DATE Sept. 22, 1980

APPROVED BY Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT # 3 DATE SEP 24 1980

CONDITIONS OF APPROVAL, IF ANY:
OGCC (3) GLE ARM (2)

