

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-5316	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
TEXACO Inc. Attention: G. L. Eaton		New Mexico Com.
3. Address of Operator		9. Well No.
P. O. Box 2100, Denver, Colorado 80201		1A
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>P</u> , <u>1190</u> FEET FROM THE <u>South</u> LINE AND <u>1080</u> FEET FROM		Blanco Mesaverde
THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>30N</u> RANGE <u>10W</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
5780' GR		San Juan


16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
		OTHER <u>Ran Liner</u> <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 2535' (55 joints) of 7" OD 20# K-55 ST&C Casing.

Set casing at 2516' KB and cemented with 305 sacks HOWCO Lite with 1/4# flo-seal and 200 sacks Class "B" with 2% CaCl₂ and 1/4# flo-seal. Bumped plug at 8:36 PM 9-8-80 with 1200 psi. Plug held. No cement to surface. Ran 1" to 65' and cemented with 50 sacks Class "B" cement with 2% CaCl₂ and 1/4# flo-seal. Cement returned to surface.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED SIGNED: G. L. EATON TITLE District Superintendent DATE Sept. 15, 1980

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE SEP 18 1980

CONDITIONS OF APPROVAL, IF ANY:
OCCC (3) CLE ARM (2)