

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
Southland Royalty Company  
3. ADDRESS OF OPERATOR  
P. O. Drawer 570, Farmington, N.M. 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1580' FNL & 1670' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)		Casing Report	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2/04/81 Ran 124 joints (4822.98') of 7-5/8", 26.40#, K-55 casing set at 4835'. DV tool at 2692'. Cemented as follows:  
1st Stage with 140 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# flocele per sack, followed with 50 sacks of Class "B" with 1/4# flocele per sack and 2% CaCl<sub>2</sub>. Plug down at 11:30 P.M. 2-4-81.  
2nd Stage with 300 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# flocele per sack, followed with 50 sacks of Class "B" with 1/4# flocele per sack and 2% CaCl<sub>2</sub>. Plug down at 2:45 A.M. 2-5-81.  
Top of cement at 700'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ethel G. [Signature] TITLE Drilling Clerk DATE Feb. 13, 1981

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY FEB 19 1981 TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

BY BL FARMINGTON DISTRICT

5. LEASE  
SF-078198  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Nye  
9. WELL NO.  
14-E  
10. FIELD OR WILDCAT NAME  
Basin Dakota/Blanco Mesa Verde  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 13, T30N, R11W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6091' GR

(NOTE: Report results of multiple completions or zone change on Form 9-330.)

