HNITED STATES

UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	SF-078198	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAM	E
1. oil gas state other	Nye 9. WELL NO.	
well well other	#14E	
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME	
Southland Royalty Company 3. ADDRESS OF OPERATOR	Basin Dakota/Blanco Mesa Verde	
P. O. Drawer 570, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	
below.)	Sec. 13, T30N, R1	
AT SURFACE: 1580' FNL & 1670' FEL AT TOP PROD. INTERVAL:	San Juan	NM
AT TOTAL DEPTH:	14. API NO.	147.1
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		· · ·
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW	DF, KDB, AND WD)
	6091' GR	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF	\	
SHOOT OR ACIDIZE	* *	
REPAIR WELL	(NOTE: Report results of m \change on Form 9-	
PULL OR ALTER CASING MULTIPLE COMPLETE		
CHANGE ZONES		
ABANDON* U Cother) Request to Sidetrack		The same of the sa
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stationary including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine	mirecinonany unineu, give su	I give pertinent dates, bsurface locations and
Propose to:		
1. Set cement retainer @ 6845' and squeeze op	en hole with 75 sad	cks of cement
with 0.6% Halad 9. 2. Perforate 2 squeeze holes at 6520'.		
3. Set cement retainer at 6435' and squeeze w Halad 9 (93% excess to cover Gallup at 615	ith 50 sacks of cer 4').	ment with 0.6%
4. PU drill pipe.		
5. Drill out retainer and dress off plug to 5	below casing.	
6. Sidetrack and drill to 7230'.		
7. Run GR-Induction and Density logs.	on Baker	
As per telephone conversation of 3-6-81 with K Subsurface Safety Valve: Manu. and Type	en baker.	t⊚ Ft.
Subsurface Safety Valve: Manu. and Type	00	
18. I hereby certify that the foregoing is true and correct		
SIGNEDTITL Dist. Prod. M		APPROVED
(This space for Federal or State	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
APPROVED BY TITLE TOTALL TO THE CONDITIONS OF APPROVAL, IF ANY:	DATE	
	MARCA	JAMES F. S DISTRICT ENGINEER
	(일간장기본 건택 의	DISTRICT LITER