UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF 078998
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
CUNDRY NOTICES AND DEPORTS ON WELLS	7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS	San Juan 32-7 Unit
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas 🔞	San Juan 32-7 Unit
well well to other	9. WELL NO.
2. NAME OF OPERATOR	#71 \$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
Northwest Pipeline Corporation	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P.O. Box 90, Farmington, N.M. 87401	Sec 9 T31N R7W = 300
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	AREA WAREA A AREA Sec 9 T31N R7W A BENEFIT
AT SURFACE: 1040' FNL & 1550' FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above	San Juan - New Mexico
AT TOTAL DEPTH: Same as above	14. API NO. = 1 = 1 6 7 6 7
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	<u>30</u> -045-24467
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6571' GR
TEST WATER SHUT-OFF	5 . 6 . 5 . 5
FRACTURE TREAT	
SHOOT OR ACIDIZE	Change on Ferm 9430.
REPAIR WELL THE PROPERTY OF	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Ferm 94830.
CHANGE ZONES \Box	ion 1 steer and steel st
ABANDON* Drilling Operations X U. S. GEOVECIE	
ABANDON* Drilling Operations X U. S. GEOLOGICAL S FARMINGTON N	about 1 IN TERM 19
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinent	all pertinent details, and give pertinent dates,
11/4/80 to 11/6/80 Drilling w/ water. Took sm	211 222 1421 2154 2154
11/4/80.	all gas kick at 5134 on the
	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
11/7/80 Ran 96 jts (3845') of 7", 2	O#. K-55 ST&C set at 3857'
Cemented with 100 sx C1 "B" 65/35 poz w/ 1	2% gel. Tailed with 75 sx
C1 "B" with 2% CaCl ₂ . Displaced plug with 151 bbls and down at 0415 hrs. WOC.	
	프로그 프로그램 기계
	# # # # # # # # # # # # # # # # # # #
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	ම්දුන්වලි එම විශ්වා එවිම්න්ට සමු මිමමෙන
SIGNED LOND Brace TITLE Production C.	lerk DATE Nov 7, 1980
(This space for Federal or State office	
ADDDOVED BY	
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE

21.24 M