

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Northwest Pipeline Corporation

3. ADDRESS OF OPERATOR
P.O. Box 90, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 810' FNL & 1750' FEL
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Drilling ☒

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

NOV 4 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330)

5. LEASE

SF 079004

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 32-8 Unit

8. FARM OR LEASE NAME

San Juan 32-8 Unit

9. WELL NO.

#42

10. FIELD OR WILDCAT NAME

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 10, T31N, R8W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

30-045-24468

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6738' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/18/80 to 10/24/80

Drilling ahead

10/25/80

Ran 19 jts of 7", 20#, K-55, ST&C and set at 4045' KB. Dowell cemented w/ 125 sx Cl "B" 65/35 poz w/ 12% gel. Tailed w/ 75-sx Cl "G" w/ 2% CaCl₂. Plug displaced w/ 160 bbls wtr and down at 1715 hrs. Wilson ran temp survey and found top of cement at 2100'. (Ojo Alamo at 2383') and PBTD at 4020'.

10/26/80 to 10/28/80

Drilling w/ gas.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Donna Brace

TITLE

Production Clerk

DATE

10/30/80

(This space for Federal or State office use)

APPROVED BY

TITLE

NMOC

DATE

CONDITIONS OF APPROVAL, IF ANY:

BW