

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER _____	7. Unit Agreement Name Farnsworth Gas Unit <i>A</i>
2. Name of Operator Energy Reserves Group, Inc.	8. Farm or Lease Name
3. Address of Operator P.O. Box 3280 - Casper, Wyoming 82602	9. Well No. 1-E
4. Location of Well UNIT LETTER <u>E</u> <u>1520</u> FEET FROM THE <u>North</u> LINE AND <u>800</u> FEET FROM THE <u>West</u> LINE, SECTION <u>17</u> TOWNSHIP <u>30N</u> RANGE <u>13W</u> NMPM.	10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) G.L. Elev. - 5,564'; K.B. - 5,578'	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER _____ <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER _____ <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The above reference well was spudded @ 9:30 a.m. 9-9-80.
 Drilled 12-1/4" hole to 370'.
 Ran 8-5/8" O.D., 24#, 8Rth, S.T. & C., R-3 new casing set @ 367' (K.B.) Cemented w/325 sx of Class "B" cement w/2% CaCl₂ & 1/4# Flocele/sx. Plug down @ 9:40 p.m. 9-9-80. Good cement returns.
 Nippled up and tested BOPE to 1,000 psi - held o.k.
 9-11-80: Drilling 7-7/8" hole to 1,700'.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R.C. Billigan TITLE Drilling Supt. - RMD DATE September 11, 1980

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT #3 DATE SEP 15 1980

CONDITIONS OF APPROVAL, IF ANY: