REPAIR WELL

ABANDON*

(other)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

As per attached letter

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES

Form 9–331 Dec. 1973	Budget Bureau No. 42-R1424		
UNITED STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	SF 079968		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a diffe	l		
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas v	Twin Mounds Federal 33		
well gas well other	9. WELL NO.		
2. NAME OF OPERATOR	#1		
Mesa Petroleum Co	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Basin_Dakota		
1660 Lincoln St., #2800, Denver, CO 80264	, ,,,		
LOCATION OF WELL (REPORT LOCATION CLEARLY. See space below.)	Sec. 33-T30N-R14W		
AT SURFACE: 1760'/N & 1785'/E	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL: Same	San Juan New Mexico		
AT TOTAL DEPTH: same	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTI	ICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5468' GR		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	Carl Man		
TEST WATER SHUT-OFF			

(NOTE: Report results of multiple completed) zo change on Form 9-3302

OIL CON. COM.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

U. S. GEOLOGICAL SURVEY

PARMINGTON, N. M.

Ran 137 joints of $5\frac{1}{2}$ " new 15.5#/ft K-55 STC casing. Landed casing @ 5943'. Cemented first stage with 20 bbls mud flush, 650 sxs 65/35 posmix with 6% gel & 10#/sx of gilsonite, 300 sxs 50/50 posmix with 2% gel & 1/4#/sx cellophane flakes. Cemented second stage with 365 sxs 50/50 posmix with 2% gel. Top of cement @ 400'.

Subsurface Safety Valve: Manua and Type			Set @	Ft.
18. I hereby certify that the foregoing is t				
SIGNED	TITLE Div. Prod. Supe	rvisbare <u>J</u> i	uly 13, 19)81
	(This space for Federal or State office	e use)		
APPROVED BY	TITLE	DATE		
CONDITIONS OF APPROVAL, IF ANY:				e e e e e e e e e e e e e e e e e e e

*See Instructions on Reverse Side

JUL 24 1981 THE THETON