REPAIR WELL

(other)

REQJEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON*

completion or zone

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Dec. 1973	Budget Bureau No. 42–R1424		
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE SF 079029		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 32-8 Unit 8. FARM OR LEASE NAME		
1. oil gas work other	San Juan 32-8 Unit 9. WELL NO. #20A		
2. NAME OF OPERATOR Northwest Pipeline Corporation 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Blanco Mesa Verde		
P.O. Box 90, Farmington, N.M. 8740] 4. OCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 4 T31N R8W		
AT SURFACE: 1560' FNL & 820' FWL AT TOP PROD. INTERVALSAME AS ABOVE	12. COUNTY OR PARISH 13. STATE New Mexico		
AT TOTAL DEPTH: Same as above 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. 30-045-24499		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6473' GR		
REQ JEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF			
EDANTURE TREAT			

change on Form 9-330.

(NOTE: Repo

Drlg operations 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give substitute locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-18-80 & 12-19-80.

Ran Induction & Neutron-Density-GR logs. Ran 75 jts (2385') of 4-1/2" 10.5#, K-55, ST&C set from 3543' to 5928'. Cemented w/ 235 sx Cl "B" w/ 4% gel & 1/4 cu.ft gils/sx. Displaced plug w/ 64 bbls of wtr. Down at 0130 hrs 12-19-80. Reversed out 20 bbls cement. Rig released at 0430 hrs 12-19-80. NOW WAITING ON COMPLETION.

Subsurface Safety Valve: Manu. and Type _			Set @	Ft.
18. I hereby certify that the foregoing is tru	ue and correct			
SIGNACCEPTED TO BY TRICED TO	TITLE Prod. Clerk	_ DATE _	12-29-80	
	(This space for Federal or State office use	e)		
APPROVED AN 0 8 1981 CONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE		
FARMINGTON DISTRICT	" weeks of the			