UNITED STATES

5 .	LEAS	E		
	NM	010989	 	

SUNDRY NOTICES AND REPORTS ON WELLS (Co not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use from 3-331-C for each proposals.) 1. oii gas gas gas of present gas of the results of multiple completion or zone change on Form 9-331-C fo	DEPARTMENT OF THE INTERIOR	NM 010989			
SUNDRY NOTICES AND REPORTS ON WELL On the use this form for proposeable to drill or to despen or plug back to a different reservoir, Use form 5-31-C for such proposals of the reservoir, Use form 5-31-C for such proposals of the reservoir, Use form 5-31-C for such proposals of the reservoir, Use form 5-31-C for such proposals of the reservoir, Use form 5-31-C for such proposals of the reservoir, Use form 5-31-C for such proposals of the reservoir of the proposals of the reservoir of the proposals of the reservoir of the proposals of the proposa	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
1. oil well Gas Gas Gas Other 2. NAME OF OPERATOR Tenneco Oil Company 3. ADDRESS OF OPERATOR F.O. Box 3249, Englewood, Colorado 80155 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1270' FNL 1270' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 18. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF GRAPH WELL GREEN GRAPH WELL GRAPH WELL GRAPH WELL GRAPH	SUNDRY NOTICES AND REPORTS ON WELLS	1			
2. NAME OF OPERATOR Tenneco Oil Company 3. ADDRESS OF OPERATOR Tobolow) 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 1270' FNL 1270' FEL. AT TOP PROD. INTERVAL: AT TOTAL DETH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FRACTURE TREAT SHOT OR ACIDIZE REPAIR WELL DULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED DEPRATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. Linerely Partify that the foregoing is True and correct Subsurface Safety Valve: Manu. and Type 18. I hereby Partify that the foregoing is True and correct SIGNED (This space for Federal or State office use)	(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME			
2. NAME OF OPERATOR Tenneco Oil Company 3. ADDRESS OF OPERATOR F.O. Box 3249, Englewood, Colorado 80155 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1270' FNL 1270' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF SHOOT OR ACIDIZE REPART WELL ORDHLETE CHANGE CONES ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11./21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/ 510sx lowco Lite. tail in w/150sx CL-B w/2% CACL2. Set slips, cut off csg. Reduce hol to 6½". Drill to TD of 7766' 11/25/80. Ran 20 jts 4½" 10.5 set @ 7766'. w/top of liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical wash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type 18. I hereby pertity that the foregame is true and correct SIGNED (This space for Federal or State office use)					
Tenneco Oli Company 3. ADDRESS OF OPERATOR P.O. Box 3249, Englewood, Colorado 80155 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 bellow.) AT SUBFACE: 1270' FNL 1270' FEL AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON' (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/510sx lowco Lite. tail in w/150sx CL-B w/28 CACL2. Set slips, cut off csg. Reduce hol of 64". Drill to TD of 7766' 11/25/80. Ran 20 jts 4½" 10.5 set @ 7766'. w/top off liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical wash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type (This space for Federal or State office use)	Well — Well Diller	9			
F.O. Box 3249, Englewood, Colorado 80155 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURRACE: 1270' FNL 1270' FEL AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP ROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA TEST WATER SHUT-OFF					
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1270' FNL 1270' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF REPACTURE TREAT SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE ULL OWNER COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work, if well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599¹. Cmt w/ 510sx dowco Lite. tail in w/150sx CL-B w/2% CACL2. Set slips, cut off csg. Reduce hol to 6½". Drill to TD of 7766' 11/25/80. Ran 20 jts 4½" 10.5 set @ 7766' w/top of liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical wash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type 18. I hereby sertify that the foregoing is true and correct SIGNED (This space for Federal or State office use)	3. ADDRESS OF OPERATOR				
Sec 28, T32N, R1lW AT SURFACE: 1270' FNL 1270' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF					
AT SURFACE: 1270' FNL 1270' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6339' gr. 16. CHECK APPROPOSED OR SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical details, and give pertinent to this work.) 18. I hereby fertify that the foregoing is true and correct subsurface locations and pertinent details, and give pertinent to this work.) 19. DESCRIBE AND TO					
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6339' gr. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, and give	10001 10001	,			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB. AND WD) 6339' gr. 15. ELEVATIONS (SHOW DF, KDB. AND WD) 6339' gr. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB. AND WD) 6339' gr. 16. CHECK APPROPOSED OF COMPLETED OF COMPLETED OF COMPLETED OF COMPLETE OF COM	AT TOP PROD. INTERVAL:	San Juan New Mexico			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF		=			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL REPAIR WELL RULL OR ALTER CASING WILTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11./21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/510sx lowco Lite. tail in w/150sx CL-B w/2* CACL2. Set slips, cut off csg. Reduce hol of 6'". Drill to TD of 7766' 11/25/80. Ran 20 jts 4½" 10.5 set @ 7766'. w/top of liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical wash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type 18. I hereby pertify that the foregoing is true and correct stopped for the property of the complex of the					
SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE SHOOT OR ACIDIZE WILL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/510sx iowco Lite. tail in w/150sx CL-B w/2% CACL ₂ . Set slips, cut off csg. Reduce hol to 64". Drill to TD of 7766' 11/25/80. Ran 20 jts 44" 10.5 set @ 7766'. w/top off liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical wash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type TITLE ASST. Div. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)	REPORT, OR OTHER DATA	The state of the s			
SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES MULTIPLE COMPLETE CHANGE ZONES Including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* L1/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/510sx lowco Lite. tail in w/150sx CL-B w/2% CACL ₂ . Set slips, cut off csg. Reduce hol to 6½". Drill to TD of 7766' 11/25/80. Ran 20 jts 4½" 10.5 set @ 7766'. w/top of liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical wash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type II. I hereby Pertify that the foregoing is true and correct slower of Federal or State office use) (This space for Federal or State office use)	REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6339 qr.			
SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES MULTIPLE COMPLETE CHANGE ZONES Including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* L1/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/510sx lowco Lite. tail in w/150sx CL-B w/2% CACL ₂ . Set slips, cut off csg. Reduce hol to 6½". Drill to TD of 7766' 11/25/80. Ran 20 jts 4½" 10.5 set @ 7766'. w/top of liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical wash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type II. I hereby Pertify that the foregoing is true and correct slower of Federal or State office use) (This space for Federal or State office use)	TEST WATER SHUT-OFF	to the second of			
REPAIR WELL PULL OR ALTER CASING WILTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1.1/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/510sx iowco Lite. tail in w/150sx CL-B w/2% CACL2. Set slips, cut off csg. Reduce hol to 6½". Drill to TD of 7766' 11/25/80. Ran 20 jts 4½" 10.5 set @ 7766'. w/top off liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical rash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type 18. I hereby pertify that the foregoing is true and correct SIGNED WILLIAMS TITLE ASST. Div. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)					
MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/510sx lowco Lite. tail in w/150sx CL-B w/2% CACL ₂ . Set slips, cut off csg. Reduce hole to 6½". Drill to TD of 7766' 11/25/80. Ran 20 jts 4½" 10.5 set @ 7766'. w/top of liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical rash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type 18. I hereby Pertify that the foregoing is true and correct SIGNED TITLE ASST. Div. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)		(NOTE: Report results of multiple completion or zone			
CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599¹. Cmt w/510sx lowco Lite. tail in w/150sx CL-B w/2* CACL ₂ . Set slips, cut off csg. Reduce hol to 6½". Drill to TD of 7766¹ 11/25/80. Ran 20 jts 4½" 10.5 set @ 7766¹. w/top off liner @ 3436¹. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical rash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE ASST. Div. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)		change on Form 9–330.)			
ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1.1/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/510sx dowco Lite. tail in w/150sx CL-B w/2% CACL2. Set slips, cut off csg. Reduce holes 64". Drill to TD of 7766' 11/25/80. Ran 20 jts 44" 10.5 set @ 7766'. w/top of liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical wash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type 18. I hereby pertify that the foregoing is true and correct SIGNED TITLE Asst. Div. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)					
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1.1/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/510sx dowco Lite. tail in w/150sx CL-B w/2% CACL ₂ . Set slips, cut off csg. Reduce hole of 6½". Drill to TD of 7766' 11/25/80. Ran 20 jts 4½" 10.5 set @ 7766'. w/top of liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical wash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED					
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* L1/21/80 Circ. & cond. Ran 86 jts. (3607') 7" 23# csg. set @ 3599'. Cmt w/510sx Howco Lite. tail in w/150sx CL-B w/2% CACL ₂ . Set slips, cut off csg. Reduce hole to 64". Drill to TD of 7766' 11/25/80. Ran 20 jts 44" 10.5 set @ 7766'. w/top of liner @ 3436'. Cmt w/250sx Howco Lite and 150 sx CL-B. Reverse out chemical wash. PD. Release rig 11/26/80. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct Signed	(other)				
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED WALLY TITLE ASST. Div. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)	including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones perting the large of	directionally drilled, give subsurface locations and ent to this work.)* 23# csg. set @ 3599¹. Cmt w/510sx Set slips, cut off csg. Reduce hole jts $4\frac{1}{2}$ " 10.5 set @ 7766¹. w/top			
18. I hereby certify that the foregoing is true and correct SIGNED LANGE TITLE ASST. Div. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)	dan. PD. Refease Try 11/20/00.	A STATE OF THE PARTY OF THE PAR			
18. I hereby certify that the foregoing is true and correct SIGNED WALLY TITLE ASST. Div. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)		de la companya de la			
18. I hereby certify that the foregoing is true and correct SIGNED LANGE TITLE ASST. Div. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)					
18. I hereby certify that the foregoing is true and correct SIGNED LIMITED TITLE ASST. Div. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)	Subsurface Safety Valve: Manu. and Type	Ft.			
SIGNED LANGE STATE ASST. DIV. Adm. MgrDATE December 10, 1980 (This space for Federal or State office use)		The state of the s			
(This space for Federal or State office use)		December 10 1980			
\cdot	SIGNED WAY OUND TITLE ASST. Div. 1	Adm MgrDATE December 10, 1900			
APPROVED BY TITLE DATE	(This space for Federal or State	office use)			
6 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	APPROVED: BY	DATE			

DEC 2 3 1980

FARMINGTON DISTRICT

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and Indian lands pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO: 1976 O - 214-149