

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
SUPRON ENERGY CORPORATION
3. ADDRESS OF OPERATOR
P.O. Box 808, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 920 ft./N ; 855 ft./W line
AT TOP PROD. INTERVAL: Same as above.
AT TOTAL DEPTH: Same as above.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

DEC 1 1980

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 12 1/4" surface hole at 7:30 p.m. 11-21-80.
2. Drilled 12 1/4" hole to total depth of 345 ft. R.K.B.
3. Ran 8-5/8", 24.00#, H-40 casing and set at 345 ft. R.K.B.
4. Cemented with 275 sx of class "B" with 2% calcium chloride. Plug down at 9:30 a.m. 11-22-80. Cement circulated to surface.
5. Waited on cement for 12 hours.
6. Pressure-tested casing to 1000 PSI for 15 minutes. Held OK.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE November 25, 1980
Kenneth E. Roddy

(This space for Federal or State office use)

APPROVED FOR RECORD
CONDITIONS OF APPROVAL

TITLE _____ DATE _____

DEC 04 1980

NMOCC

FARMINGTON DISTRICT

*See Instructions on Reverse Side