

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Tom Bolack
3. ADDRESS OF OPERATOR
P.O. Box 255, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 790 ft. from S & W lines
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
JAN 10 1981
U. S. DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

(NOTE: Report results of multiple completion or zone change on Form 9-330.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well 8:30 p.m., January 6, 1981. Drilled 13 3/4" hole to 263 ft. Ran 6 jts. 9 5/8", 36.0#, J-55, ST&C surface casing, landed at 255 ft. Cemented surface casing with 275 sacks Class B cement with 2% CaCl₂, 1/2 lb./sack cellophane flakes. Good Circulation throughout job, circulated 90 sx. to surface. Plug down 9:00 a.m., 1/7/81. Nippled up BOP's and pressure tested to 1600 psi and held.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED



TITLE Agent

DATE

January 8, 1981

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE


CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NMOCC

JAN 08 1981

*See Instructions on Reverse Side

BY  FARMINGTON DISTRICT