

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR

Northwest Pipeline Corporation

3. ADDRESS OF OPERATOR

P.O. Box 90, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1600' FSL & 180' FEL

AT TOP PROD. INTERVAL: Same as above

AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Drilling Operations ☒

SUBSEQUENT REPORT OF:

RECEIVED
NOV 25 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE

SF 078996

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 32-7 Unit

8. FARM OR LEASE NAME

San Juan 32-7 Unit

9. WELL NO.

#74

10. FIELD OR WILDCAT NAME

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 4 T31N R7W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6744' GR

E: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/14/80 to 11/19/80 Drilling ahead

11/20/80 Ran 97 jts of 7", 20#, K-55, ST&C and set at 3952'. Howco cemented w/ 175 sx 65/35 poz w/ 12% gel, tailed w/ 75 sx C1 "B" w/ 2% CaCl₂. Displaced plug with 160 bbls of water and down at 0515 hrs. Wilson ran temp survey and found top of cement at 1550' (ojo Alamo 2487') w/ PBTD at 3820'.

11/21/80 to 11/22/80 Drilling ahead.

11/23/80 GO ran IES/GR & SNP/CDL/GR Logs. Gauged well at 5712', 5954', & 6200' w/ no shows. Ran 80 jts (2443') of 4-1/2", 10.5#, K-55, ST&C and set from 3757 to 6200'. Howco cemented w/ 240 sx C1 "B" w/ 4% gel & 12.5# fine gill/sx. Reversed out 7 bbls of cmt. Plug displaced with 66.5 bbls of Subsurface Safety Valve Manu and Type Set @

18. I hereby certify that the foregoing is true and correct

wtr and down at 2230 hrs. Rig released at 0300 hrs 11/24/80

SIGNED Donna Brace TITLE Production Clerk DATE 11/24/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOC