Original + 2

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator Thurus Exploration INC.		Lease fl		Well 8-4				
eation Well: Unit C Sec. 18 Twp. 201		Rge		County SAV JUN				
NAME OF RESERVOIR OR P	POOL	TYPE OF PR		ETHOD OF PROD. Flow or Art. Lift)	PROD, MEDIUM (Tog. or Cag.)			
Completion Pictured Cliff		Jac	Jac		Tbg			
Completion Mesa Verte		GAS		Flow	Tba			
	PRE-FLOW	SHUT-IN PR	ESSURE DATA		J			
Upper 7:350 m 1-13-48	again of time shut-in	Smir	Si prote pale	9-247	Stabilized? (Yes or No) Stabilized? (Yes or No)			
Completion 2:35pm 7-13-98	13 Hr. 51	n wing 1	Tbg-419					
	-kn	FLOW TEST I		/ N	1.1			
Consmenced at (hour, date) * 4.75 0 M 1-16-	PRESSUR	RE	Zone producing (Upp PROD. ZONE	er or Lowest	.٧			
	er Completion I	Lower Completion	TEMP.	M. st 1500	REMARKS			
1:000m 7-1799 22/11 35 micsa-	747	69-282		11110				
9:00Am 7-18-98 38 Hrs 35min CR2	247	ba-164			(2) (2)			
P.C zare ov P. 9:02 Am		-		7 15.5 Jil	WEIVED			
					2 2 1998 (P)			
				(9)[[[]	GOM, DINY			
					Plate 3			
				<u> </u>				
Production rate during test								
Oil: BOPD bas	sed on	Bbls. in	Hours.	G	rav GOR			
Gas: MCFPD; Tested thru (Orifice or Meter):								
MID-TEST SHUT-IN PRESSURE DATA								
Upper Completion	ength of time shut-in		Si press. psig		Stabilized? (Yes or No)			
	ength of time shut-in	1	SI press. peig		Stabilized? (Yes or No)			

FLOW TEST NO. 2

				zone producing (Upper or Lower):		
TIME (how, date)	LAPSED TIME		SURE	PROD. ZONE	REMARKS	
	SINCETT	Upper Completion	Lower Completion	TEMP.	REMARKS	
			1			
 		<u> </u>	100000000000000000000000000000000000000			
		 		}		
		}	İ	}		
		 				
	1		` '.		,	
		 	<u> </u>			
		?				
roduction rate	during ter				· · · · · · · · · · · · · · · · · · ·	
oduction rate	dmm8 test					
il:	BOP.	D based on	Bhl. :-	**		
		D D25cd Oil	DUS. III	Hours.	Grav GOR	
25:		МСЕ	PD: Tested that	(Orifice or Massa):	
			. D. Tested dill	Counce of Meter): 	
:marks:				, ·		
			*			
				_	,	
•		• :				
hereby certify	that the information	on herein contain	ed is true and co	mplete to the nes	Fof my knowledge.	
	JUL 2	3 199 ₀				
pproved	**	3 1990	_19 C	perator	lagrap Exploration Inc. U.	
New Mexico (Oil Conservation D	Division				
	Chring &	Shinger	В	y (Manaa	Likm	
	J-		•	, –		
	Germy & Doputy Oil &	Gas-Inspector	T	ide <u>UASC</u>	Operator	
tle _		•		ate 01118		
				ate) /I N	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage ten shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at thour date) ##

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leskage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).