

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT 9 10 11

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD

\((806) 334-6178 FAX: (806) 334-6170

Page 1 Revised 11/16/98

_	NOI	RTHWEST NE	W MEXICO	PACKE	LEAKAGE TEST		
Operator	verger Leso	urces	_Lease Nan	no Aztec	1.5000000000000000000000000000000000000	Weil No	
ocation of	Well:Unit Letter_	M_sec_9	_Twp_30N	Rge IIV	/_API#30-045-246	95	
	NAME OF RESE	TYPE OF PROD. (Oil or Gas)		METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)		
Upper Completion	P.C. Fot	Gae		Flow	Tha		
Lower Completion	N.v'	CAS		flow	1 1bg		
	. = =	PRE-FL	ILTUH8 WO.		E DATA		
Upper Completion	Hour, date shut-in	Length of time	'n	Si press. Paig D-172 (0-175	Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in	16 01	Length of Bine		St press, Psig '	Stabilized? (Yes or No)	
Commenced at (hour, date)* (0:30 A:	m 11119161	FLOW TE		(Upper of Lower):		
TIME (hour,date)	LAPSED TIME SINCE*	E PROD. ZON TEMP.					
:30 11 20 01		to-174 co-176-to	- 934 -784		Lower Zore Flowed		
1:00 11 21 61 1:00 11 22 10	2642 Hrs	to-176 co-176 to	1-289 1-280		·		
roduction ra	te during test						
		BOPD based or	n	Bbls. in	HoursGra	avGOR	
Gas:		MCFPD	; Tested thru	(Orifice or M	leter):	,	
	·	MID-TE	ALTUH2 TE	PRESSURI	E DATA		
Upper Completion	Hour, date shut-in	Length of time shut-in		SI press psig	Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in	Length of time shut-in		SI press. psig	Stabilized? (Yes or Nn)		

			FLOW TI	8T NO. 2				
Commence	d at (hour, date)	•		Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**	PRESURE Upper Completion Lower Completic		PROD. ZONE	REMARKS			
 	<u> </u>							
Production ra	te during test							
Oil: Gas:	BOPD	based onMCFF	Bbls. PD:Tested thru (C	. inHour	sGravGOR			
			·					
hereby certif	y that the inform	nation herein cor	ntained is true and	complete to the	bes of my knowledge.	-		
A <mark>pproved</mark> Mexico Oil Con	servation Division	19	- abaiator-	17.	ves of my knowledge.	_ New		
	•		By VANH	ry Batters	······································			
By	M SAMED DV CH	AND T. PRIVAN	1	se Operatore				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

MANUTY ON & BAS INSTRUCTOR, BIBL &

By

Title

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified,
- 3. The packer leakage test shall commence when both zones of the dual completion are shul-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone lests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.

24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).