UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF-080244
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1 ail gos —	Riddle Com
1. oil gas well other	9. WELL NO.
2. NAME OF OPERATOR	8
Tenneco Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota
P. O. Box 3249, Englewood, CO 80155	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LCICATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec. 18, T30N R9W
AT SURFACE: 1630' FSL 790' FEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE San Juan New Mexico
AT TOP PROB. INTERVAL. AT TOTAL DEPTH:	
	14. API NO.
16. CHECK APPROPRIATE BOX TO NDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15 ELEVATIONS (CHOW DE KDP AND WD)
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6223' gr.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	0223 g1.
TEST WATER SHUT-OFF	engin it
FRACTURE TREAT	NAPO A
Shoot on holder	
REPAIR WELL PULL OR ALTER CASING	(NOTE: Report results of multiple to hip et an or 20 hip change on Form 9-380
MULTIPLE COMPLETE	/ Illeman
CHANGE ZONES	0CT 7 - 1981
ABANDON*	OIL CON. COM.
(other)	OIL CON. 3
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statisticized including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine 9/21/81 - MIRUSU.	te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and
9/22/81 - Killed well w/l% KCL water. NDWH.	NUBOP. Unseat pkr and POOH w/tbo
and pkr.	_
9/23/81 - Acidize w/1700 gals 15% weighted Ho	CL and 73 1.1 ball slrs. Ball off
complete. Round trip junk basket rec'd 73 basket XL gel and 160,000# 20/40 sand. AIR 55 labeled in SIP 1050 psi.	alls. Frac'd Dakota w/93,000 gals BPM, AIP 3000 psi, ISIP 1650 psi,
9/24/81 - RIH w/tbg, pump out plug and SN.	Tagged sand fill @ 7400'. Clean
out to PBTD w/foam. Landed tbg @ 7258'. ND	
around w/N2.	
O. L. C. C. Cafeb. Webser Manus and Tuno	Set @ Ft.
Subsurface Safety Valve: Manu. and Type  18. I hereby certify that the foregoing is true and correct	
	Analystate 9/28/81
(This space for Federal or State o	
*·*· =	DATE
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
	* · · · · · · · · · · · · · · · · · · ·
	4 4

\*See Instructions on Reverse Side

JCT 6 190°