5. LEASE

## UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	NM 04375
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas G	Reid "A"
well well other	9. WELL NO.
2. NAME OF OPERATOR	1-E
SUPRON ENERGY CORPORATION	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota
P.O. Box 808, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.)	Sec. 1, T-30N, R-13W, N.M.P.M.
AT SURFACE: 900 ft./S ; 1850 ft./E line	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above	San Juan New Mexico
AT TOTAL DEPTH: Same as above	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	
TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone SURVEY change on Form 9-330.) R 2 17 1981
PULL OR ALTER CASING []	change on Form 9-330.) R 2 17 100
MULTIPLE COMPLETE	SURVE COLL 1987
CHANGE ZONES	S. D. Co. 2 90/2
ABANDON*	\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
(other) U. Sellin and the sellin and	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	e all pertinent details, and give pertinent dates, irectionally drilled, give subsurface locations and
1. Spudded 12-1/4" surface hole at 11:00 a.m	
2. Drilled 12-1/4" surface hole to total dep	th of 298 ft. R.K.B.
3. Ran 6 joints of 8-5/8", 24.00#, H-40 casi	ng and set at 287 ft. R.K.B.
4. Cemented with 200 sacks of class "B" with down at 9:00 p.m. 4-15-81. Cement circul	3% calcium chloride. Plug ated to surface.
5. Waited on cement for 12 hours.	
6. Pressure-tested casing to 1000 P.S.I. for	15 minutes. Held OK.
	Sat ©
Subsurface Safety Valve: Manu. and Type	set @ rt.
18. I hereby certify that the foregoing is true and correct	ant April 20, 1981
SIGNED Kenneth E. Roddy  (This space for Federal or State offi	
/	DATE
APPROVED BY TITLECONDITIONS OF APPROVAL, IF ANY:	DATE
	1256 P. J. 103 238080

APR 24 1981