

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ well other

2. NAME OF OPERATOR
Tenneco Oil

3. ADDRESS OF OPERATOR
P.O. Box 3249 Englewood CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1520 FSL 1405 FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE

SF - 077833

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mansfield Com

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 30 T30N R9W

12. COUNTY OR PARISH

San Juan


13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5971 ground

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/19/81 MIRURT. Spud well on 7-18-81 with Four Corners #7. Drill 12 1/4" hole to 295'. RU & run 7 joints (283') 9-5/8" 36# K-55 ST&C. Set @ 294' cement with 250 SX class-B & 2% CACL2 & 1/4#/SX celloflake. Circ cement to surface. NUBOP & test to 100 PSI for 30 min. O.K.

7/26/81 TD of 7192' Ran 94 joints 4-1/2" K-55 ST&C (213') 11.6# & (4108') 10.5#CSG. Set @ 7191'. Float collar @ 7147' Top of liner @ 2857 cement with 370 SX BT lite & .6# D-19 & .490 R-11. Tail with 150 SX class-B & same additives Release Vig

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Production Analyst DATE 7/28/81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC