

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Blackwood & Nichols Co., Ltd.
3. ADDRESS OF OPERATOR  
P. O. Box 1237, Durango, Colorado 81301
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 790' F/SL - 1190' F/WL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO:                                      | SUBSEQUENT REPORT OF:    |
|---|--------------------------|
| TEST WATER SHUT-OFF <input type="checkbox"/>                  | <input type="checkbox"/> |
| FRACTURE TREAT <input type="checkbox"/>                       | <input type="checkbox"/> |
| SHOOT OR ACIDIZE <input type="checkbox"/>                     | <input type="checkbox"/> |
| REPAIR WELL <input type="checkbox"/>                          | <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/>                 | <input type="checkbox"/> |
| MULTIPLE COMPLETE <input type="checkbox"/>                    | <input type="checkbox"/> |
| CHANGE ZONES <input type="checkbox"/>                         | <input type="checkbox"/> |
| ABANDON* <input type="checkbox"/>                             | <input type="checkbox"/> |
| (other) <u>Recomplete</u> <input checked="" type="checkbox"/> |                          |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Due to excessive water, we propose to squeeze cement the existing perforations at 3518', 3529', 3537', 3549'. Perforate 4 holes per foot per interval 3572', 3580', 3584', 3608'. Set a packer on 2 3/8" tubing at 3560'. Foam fracture (70% nitrogen - 30% water) and 75,000 lbs. 20-40 sand. Test zone for quantity gas and water.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE District Manager DATE May 10, 1982

APPROVED BY [Signature] (This space for Federal or State office use)

APPROVED BY [Signature] TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL IF ANY: MAY 11 1982  
JAMES F. SIMS  
DISTRICT ENGINEER