

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410

(505) 334-6176 FAX: (505) 334-6170 http://emnrd.state.nm.us/ocd/District III/3distric.ht

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator 2	op America P 2 <mark>00 Energy</mark> C	roduction t, Farming	Company ato lease Na r	me Cold	Liron C	om A	Well No_in	
•	Well:Unit Letter						4941	
	NAME OF RESE	TYPE O	TYPE OF PROD.		OF PROD.	PROD.MEDIUM		
				(Oil or Gas)		Art. Lift)	(Tbg. or Csg.)	
Upper Completion	Blanco	GA:	GAS		DW	TBG		
Lower Completion	Basin	DK	GA:	GAS)W	TBG	
		PRE	-FLOW SHUT-I		RE DATA St press. Psig			
Upper	Hour, date shut-in		1 -	Length of time shut-in			Stabilized? (Yes or No)	
Completion	9/17	<u>/02</u>	72 HO		247 SI press. Psig		YES Stabilized? (Yes or No)	
Lower	Hour, date shut-in		Length of time 72 HOU		Si press. Psig		YES	
Completion	9/17	/ 0a		ST NO. 1	<u> </u>)		
Commenced at ((hour, date)*		:	Zone producing	(Upper or Lower);		
TIME (hour,date)	LAPSED TIME SINCE*	PRESSURE		PROD. ZON	E	RE	EMARKS	
		Upper Completion	Lower Completion	TEMP.				
9/17	DAY 1	213	348	В0		TH ZONES SHUT IN		
9/18	DAY 2	241	611	BOTH ZONE		ZONES SH	SHUT IN	
9/19	DAY 3	247	625	BOTH ZONES S		ZONES SH	UT IN	
9/20	DAY 4	a 50	273	FLOW Lower		Lower	ZONE	
9/21	DAY 5	253	126		FLOW	111	ZONE	
9/22	DAY 6	a55	125		FLOW	11	ZONE	
	ate during test							
Oil:	-	d on	Bbls. in	Hours	Grav	vGOR		
Gas:		MCF	PD; Tested thru	(Orifice or M	leter):			
		MID	-TEST SHUT-IN	I PRESSURI	E DATA			
Upper	T.,	1 4 4	Length of time shut-in			Stabilized? (Yes or No)		
Completion	Hour, date shut-in		Length of time :	Stiut-in	SI press psig		ĺ	

(Continue on reverse side)

FLOW TEST NO. 2

Commence	d at (hour, date)			Zone producing (Upper or Lowr):			
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS		
							
			Bbls. D:Tested thru (Or		sGoR		
l hereby certify	that the inform	ation herein cont	tained is true and	complete to the b	pes of my knowledge.		
Approved1919		_ Operator	Amoco Prod	duction Company	New		
	production of a transfer of the second			Sheri Brad	dshaw 83		
Ву <u></u>					1	-	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the rormal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an cil well. Note: if, on an initial
- racker leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5 Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).