

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT LOG *

1a. TYPE OF WELL:		OIL WELL ☐	GAS WELL ☒	DRY ☐	Other ☐		
b. TYPE OF COMPLETION:		NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF. RESVR. ☐	Other ☐
2. NAME OF OPERATOR SUPRON ENERGY CORPORATION							
3. ADDRESS OF OPERATOR P.O. Box 808, Farmington, New Mexico 87401							
4. LOCATION OF WELL (Report location clearly and in accordance with <i>any State requirements</i>) At surface 1520 ft./N ; 810 ft./W line At top prod. interval reported below Same as above At total depth Same as above							
14. PERMIT NO. ☐ DATE ISSUED ☐							
15. DATE SPUDDED 8-25-81							
16. DATE T.D. REACHED 9-5-81							
17. DATE COMPL. (Ready to prod.) 12-30-81							
18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 5756 R.K.B.							
19. ELEV. CASINGHEAD 5745							
20. TOTAL DEPTH, MD & TVD 6544 MD & TVD							
21. PLUG, BACK T.D., MD & TVD 6498 MD & TVD							
22. IF MULTIPLE COMPL., HOW MANY* ---							
23. INTERVALS DRILLED BY ---							
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 6324 - 6441 Dakota (MD & TVD)							
25. WAS DIRECTIONAL SURVEY MADE No							
26. TYPE ELECTRIC AND OTHER LOGS RUN Induction Electric and Compensated Density							
27. WAS WELL CORED No							
28. CASING RECORD (Report all strings set in well)							
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED		
8-5/8"	24.00	448	12-1/4"	250 sacks			
4-1/2"	10.50	6544	7-7/8"	750 sacks (2 stages)			
29. LINER RECORD							
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	PACKER SET (MD)		
30. TUBING RECORD							
SIZE	DEPTH SET (MD)	PACKER SET (MD)					
2-3/8"EUE	6391	--					
31. PERFORATION RECORD (Interval, size and number) 1 - 0.42" hole at each of the following depths: 6324, 28, 32, 34, 82, 84, 92, 6405, 08, 11, 16, 18, 21, 24, 26, 37, 39, 41. Total of 18 holes.							
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.							
DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED						
6324 - 6441	1500 gal. 7 1/2% HCL, 72,700 gal. 75% foam w/20 lb. gelled water, 3190 SCF N ₂ , & 81,560 lb. 20-40 sand. All fluid contained 2% KCL water.						
33.* PRODUCTION							
DATE FIRST PRODUCTION	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing	WELL STATUS (Producing or shut-in) Shut-In					
DATE OF TEST 12-30-81	HOURS TESTED 3	CHOKE SIZE 3/4"	PROD'N. FOR TEST PERIOD ---	OIL—BBL. ---	GAS—MCF. 316	WATER—BBL. ---	GAS-OIL RATIO ---
FLOW. TUBING PRESS. 208	CASING PRESSURE 818	CALCULATED 24-HOUR RATE ---	OIL—BBL. ---	GAS—MCF. 2530	WATER—BBL. ---	OIL GRAVITY-API (CORR.) ---	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Vented							
35. LIST OF ATTACHMENTS							
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.							
SIGNED <u>Kenneth E. Roddy</u> Kenneth E. Roddy		TITLE <u>Production Superintendent</u>		DATE <u>December 31, 1981</u>			

*(See Instructions and Spaces for Additional Data on Reverse Side)

NMOCC

BY Smm
FARMINGTON DISTRICT

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:			38. GEOLOGIC MARKERS		
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES		DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
FORMATION	TOP	BOTTOM			
			Ojo Alamo	233'	
			Kirtland	383'	
			Fruitland	1470'	
			Pictured Cliffs	1782'	
			Chacra	2715'	
			Cliff House	3347'	
			Point Lookout	4162'	
			Gallup	5455'	
			Greenhorn (Base)	6270'	
			Dakota	6316'	