

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

WEXPRO COMPANY

3. Address and Telephone No./O CELSIUS ENERGY COMPANY (303) 296-8945

1125-17TH STREET, SUITE 2240, DENVER, COLORADO 80202

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SE/4 SE/4 SECTION 27 T30N-R14W
1050' FSL; 1060' FEL

5. Lease Designation and Serial No.

NM - 4465

6. If Indian, Allottee or Tribe Name

7. If Land or C.A. Agreement Designation

8. Well Name and No.

GREG #1

9. API Well No.

10. Field and Pool, or Exploratory Area

DAKOTA

11. County or Parish, State

SAN JUAN, NEW MEXICO

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Interest
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

PLUGGING AND ABANDONMENT OPERATIONS ON THE ABOVE-CAPTIONED WELL WERE COMPLETED 6/30/92 AND WITNESSED BY LEONARD BIXLER, BLM - FARMINGTON

1. SET CEMENT RETAINER AT 5600'
2. PLUG #1 5600'-5466' 10 SX CL-B (15.6 PPG) SPOTTED ABOVE CEMENT RETAINER IN 4-1/2" CASING.
3. PLUG #2 4,909'-4,681' 17 SX CL-B (15.6 PPG) SPOTTED INSIDE 4-1/2" CASING.
4. PERFORATE 2 HOLES AT 2,734', SET CEMENT RETAINER AT 2,630'.
5. PLUG #3 2,734'-2,500' 56 SX CL-B (15.6 PPG) inside and outside 4-1/2" CASING.
6. PERFORATE 2 HOLES AT 1,183', SET CEMENT RETAINER AT 1,083'.
7. PLUG #4 1,183'-950' 56 SX CL-B (15.6 PPG) INSIDE AND OUTSIDE 4-1/2" CASING.
8. PERFORATE 2 HOLES AT 580'
9. PLUG #5 580'-SURFACE 176 SX CL-B (15.6 PPG) CIRCULATED TO SURFACE INSIDE AND OUTSIDE 4-1/2" CASING.
10. PLUG #6 SURFACE PLUG 15 SX CL-B (15.6 PPG) TO INSTALL DRY HOLE MARKER AFTER CUTTING OFF THE WELLHEAD.

NOTE: 9.0 PPG, 50 VIS MUD WAS SPOTTED IN CASING BETWEEN CEMENT PLUG.

**OPERATOR REQUESTS SURFACE REHABILITATION INSTRUCTIONS

14. I hereby certify that the foregoing is true and correct

Signed

(This space for Federal or State office use)

Title DISTRICT MANAGER

Date 7/14/92

Approved by

Conditions of approval, if any:

Title

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

Date

APPROVED

JUL 20 1992

AREA MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

NMOOD