UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF 078214
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	McCord
Well - Well Other	9. WELL NO. 4-E
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME
SUPRON ENERGY CORPORATION	Basin Dakota
3. ADDRESS OF OPERATOR P.O. Box 808, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec. 22, T-30N, R-13W, NMPM
AT SURFACE: 790 ft./N ; 895 ft./W line	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above	San Juan New Mexico
AT TOTAL DEPTH: Same as above	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15 51 51 51 51 51 51 51 51 51 51 51 51 5
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3360 R.A.B.
TEST WATER SHUT-OFF RECEIVE	VED
SHOOT OR ACIDIZE SHOTT OR ACIDIZE SHOTT OR ACIDIZE SHOTT OR ACIDIZE SHOTT	(NOTE: Report results of multiple grant and at some
	change on Horm 9-3300 *** # # # 1 1 1
MULTIPLE COMPETE	AL SURVEY
CHANGE 201423	1012 CON 1587 /
ABANDON*	1 No. 1
	9/57: 300.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	irectionally drilled, give subsurface locations and
1. Spudded 12½" hole at 6:00 a.m. 5-30-81.	·
2. Drilled 12½" hole to total depth of 289 f	t. R.K.B.
3. Ran 6 joints of 8-5/8", 24.00#, H-40 casi	
4. Cemented with 200 sacks of class "B" w/3%	s calcium chloride. Plug
down at 11:15 a.m. 5-30-81. Cement circu	lated to the surface.
5. Waited on cement for 12 hours.	
6. Pressure-tested casing to 800 PSI for 15	minutes. Held UK.
Subsurface Safety Valve: Manu. and Type	Set @ Ft
18. I hereby certify that the foregoing is true and correct	
SIGNED Renneth E. Roddy (This space for Federal or State off	upt. date <u>June 1, 1981</u>
(This space for Federal or State of	fice use)
	DATE
CONDITIONS OF APPROVAL, IF ANY:	