

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR  
*SUPRON ENERGY CORPORATION*

3. ADDRESS OF OPERATOR  
*P.O. Box 808, Farmington, New Mexico 87401*

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: *820 ft./N ; 1525 ft./W line*  
AT TOP PROD. INTERVAL: *Same as above*  
AT TOTAL DEPTH: *Same as above*

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) *Ran 4½" casing*

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE

*SF 078214*

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

*McCord*

9. WELL NO.

*3-E*

10. FIELD OR WILDCAT NAME

*Basin Dakota*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

*Sec. 34, T-30N, R-13W, N.M.P.M.*

12. COUNTY OR PARISH 13. STATE

*San Juan New Mexico*

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

*5694 R.K.B.*

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 1. Drilled 7-7/8" hole with mud to total depth of 6425 ft. R.K.B. Total depth was reached on 8-11-81.*
- 2. Ran 157 joints of 4½", 10.50#, K-55 casing and set at 6425 ft R.K.B. with float collar at 6386 ft. R.K.B. Stage collar was set at 4364 ft. RKB.*
- 3. Cemented first stage with 350 sacks of 50-50 POZ mix w/2% gel & 10% salt. Plug down at 3:15 a.m. 8-13-81. Cemented second stage w/550 sacks of 65-35-12 w/12½ lb. of gilsonite per sack and 50 sacks of class "B" w/ 2% calcium chloride. Plug down at 8:15 a.m. 8-13-81.*
- 4. Ran temperature survey and found cement top at 200 ft. R.K.B.*

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Kenneth E. Roddy* TITLE *Production Supt.* DATE *August 19, 1981*  
*Kenneth E. Roddy*

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

\*See Instructions on Reverse Side

NMOCC

