

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR  
William C. Russell

3. ADDRESS OF OPERATOR  
227 E. 59th St., New York, NY 10022

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1190' FSL & 1520' FEL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input checked="" type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

RECEIVED

SEP 01 1983

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

SEP 1 - 1983

N. DIV.

Dist. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-22-83 to 8-25-83

Circulated cement from 4525 ft. to the surface to repair D.V. tool failure when well was drilled. Pumped 1000 sx (1850 ft<sup>3</sup>) of Halliburton "light" cement containing 12½ lbs. gilsonite per sack followed by 50 sx (59 ft<sup>3</sup>) of Class B cement with 2% CaCl through perforations at 4525 ft (below D.V. tool @ 4510 ft). Circulated cement to the surface. Drilled out cement in casing and pressure tested to 1000 psi. Held OK. Returned well to production.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kevin H. McCou TITLE Agent DATE September 1, 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 02 1983

\*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY KI

NMOCC