STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

2,10, 2.10		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE	l	
OPERATOR	T	[

OIL CONSERVATION DIVISION P. O. BOX 2088

fora	C-1	0.1	
Boute	e d	10-	1 - 78

[SANTA FE	SANTA FE, P	NEW MEXICO 87501			
Ī	FILE			5a. Indicate Type of Lease		
Ì	U.S.G.S.			State X Fee		
ţ	LAND OFFICE		•	5. State Otl & Gas Lease No.		
Ī	OPERATOR			V-100		
				mmmmmm.		
	SUN GOD HOT USE THIS FORM FOR	NDRY NOTICES AND REPORTS	S ON WELLS	7. Unit Agreement liane		
	OIL CAS X	07HER-	11982 - 11982			
	ne of Operator		3000	8. Form or Lease Hame		
	upron Energy Corp.		OIL CON COM	State Com. 31-8		
			Dis	9. Well No.		
3. Ad	iress of Operator	Ington, New Mexico 8740		1		
		ing con, New Hexico C140		10. Field and Pool, or Wildcat		
4. Lo	cation of well			Blanco Mesaverde; Basin I		
١,	INIT LETTERM	905 PEET FROM THE SOU	th LINE AND 790 FE	TITITITITITITITITITITITITITITITITITITI		
`	, <u>-</u>					
	HE West LINE, S	ECTION TOWNSHIP	31N RANGE 8W	_ HMPM. (
'	**		27.69	12. County		
111			hether DF, RT, GR, etc.)			
		6616 R.K.	В	San Juan		
16.	Che	ck Appropriate Box To Indica	ate Nature of Notice, Report	or Other Data		
		F INTENTION TO:	subse	QUENT REPORT OF:		
	NOTICE	F INTENTION TO				
TEMP	HOGHABA VIJEARO	PLUG AND ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS.	ALTERING CASING PLUG AND ABANDONMENT		
PULL	OR ALTER CASING	-	OTHER Deviated ho	le & ran 53" Liner		
			- 🗆 l			
01	THER					
17. D	ork) SEE RULE 1103.			ncluding estimated date of starting any proposed		
1.	Drilled 6 3/4" ho	ole with gas to 8108 ft.	R.K.B.			
2.	Twisted off drill	L pipe at 1771 ft. R.K.B	•			
3.	Shot off drill pi	ipe at 8050 ft. R.K.B.				
4.	Stuck fishing tools at 8043 ft. and mudded up hole.					
.5.	Could not recover fish. Backed off drill pipe at 8045 ft. R.K.B. Left in the hole the bit, bi					
	sub square drill	l coller, round drill co	llar, and bumper subs.			
6.	Pumped 100 sacks	of class "H" with 35% s	ilica flour and 2% fric	tion reducer. Plug in place at		
	9:30 A.M. 5/17/82	Dressed top of cement	plug to 7800 ft.			
7.	Rep. 6.3//" diamond bit and $2\frac{1}{7}$ bent sub. Drilled to 7859 ft.					
8.	\mathcal{L}_{-} . L					
-	5/25/82.					
9.	D- TEC COT CNI	logs.		(2200 at) a rlu 45 ro#		
10.	Ran 27 inints (11	1/8 ft.) of 5½". 17.00#.	K-55 casing and 55 joi	nts (2300 ft.) of $5\frac{1}{2}$ ", 15.50#,		
	K-55 casing and s	set at 8352 ft. R.K.B. F	Toat collar set at 8305	ft. R.K.B. Top of liner		
	hanger was set at	t 4904 ft. K.K.B.	and a second	1 + 5.20 B.W. 5/26/92		

	handed and belief	
18. I hereby certify that the information above is true and con	mplete to the pest of my knowledge and persen-	
DIENER Kenneth E. Koddy	YHLE Production Superintendent	DATE June 9, 1982
Criginal Signed by CHARLES GHOLDON	DEPLITY ON & GAS INSPECTOR, DIST. #3	0 11.1982

11. Cemented liner with 450 sacks of 50-50 Pozmix with 2% gel. Plug down at 5:30 P.M. 5/26/82.