

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
Supron Energy Corporation

3. ADDRESS OF OPERATOR  
P.O. Box 808, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1120 Ft./S; 790 ft./East line  
AT TOP PROD. INTERVAL: Same as above  
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
SF 078510

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Oxnard

9. WELL NO.  
4

10. FIELD OR WILDCAT NAME Wildcat  
Pump Mesa Fruitland Ext.- P.C.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 8, T-31N, R-8W, N.M.P.M.

12. COUNTY OR PARISH San Juan 13. STATE New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6557 Ft. R.K.B.

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☒  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

We desire to dually complete this well as a Pictured Cliffs and Farmington Sand instead of a Pictured Cliffs and Fruitland well due to the Fruitland zone being to wet to produce. All aspects of the original A.P.D. will be complied with, with the exception of perforating and fracturing the Fruitland zone. We will perforate the Farmington Sand and stimulate proudction at 2640 feet.


Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Rudv D. Motto TITLE Area Supt. DATE November 18, 1981

(This space for Federal or State office use)  
(Orig. Sgd.) RAYMOND W. VINYARD RAYMOND W. VINYARD  
APPROVED BY \_\_\_\_\_ TITLE ACTING DISTRICT SUPERVISOR DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

NOV 19 1981



\*See Instructions on Reverse Side

NMOCC