

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR LAURENCE C. KELLY		8. FARM OR LEASE NAME Kelly Brothers	
3. ADDRESS OF OPERATOR c/o Walsh Engr. & Prod. Corp. P. O. Box 254 Farmington, N.M.		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1590' FSL, 1640' FWL		10. FIELD AND POOL, OR WILDCAT Blanco Pictured Cliffs	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 8-T30N-R10W N.M.P.M.	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6289' GL		12. COUNTY OR PARISH San Juan	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
(Other) <input type="checkbox"/>	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF <input checked="" type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
(Other) <input type="checkbox"/>	

(NOTE: Report results of multiple completion on Well Completion or Recompilation Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

8/17/81 Spud Well  
7/18/81 T.D. 121'. Ran 3 joints 8-5/8", 24.0 lb., K-55 casing (118') set at 120' with 100 sacks Class "B" cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated. Pressure test with 500 psig. Test ok.  
8/22/81 T.D. 3060'. Ran 71 joints 4-1/2", 10.50 & 11.60, K-55 casing (3064') set at 3060' with:  
330 sacks 65-35 Pozmix with 12% Gel with 6-1/4 lbs. Gilsonite per sack, followed by 310 sacks 50-50 Pozmix with 3% Gel and 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack. Cement circulated to surface.

FOR: LAURENCE C. KELLY

18. I hereby certify that the foregoing is true and correct

SIGNED

EWELL N. WALSH, P.E.

TITLE

President, Walsh Engr. & Production Corp.

DATE

8/31/81

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

NMOCC

