

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. SF-077754
2. NAME OF OPERATOR LAURENCE C. KELLY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR c/o Walsh Engr. & Prod. Corp. P.O. Box 254 Farmington, N.M. 87401		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with State requirements. See also space 17 below.) At surface 1490'PSL, 1560'FEL		8. FARM OR LEASE NAME Kelly Brothers
14. PERMIT NO.		9. WELL NO. 2
15. ELEVATIONS (Show whether P.S., RT., GR., etc.) 6405'GL		10. FIELD AND POOL, OR WILDCAT Blanco Pictured Cliffs
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 8-T30N-R10W N.M.P.M.
		12. COUNTY OR PARISH San Juan
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/22/81 Spud Well

8/22/81 T.D. 135'. Ran 3 joints 8-5/8", 24.0 lb., K-55 casing (122') set at 136' with 100 sacks Class "B" cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated. Pressure test with 500 psig. Test ok.

8/27/81 3200'. Ran 75 joints 4-1/2", 10.50 & 11.60, K-55 casing (3202') set at 3199' with:

330 sacks 65-35 Pozmix with 12% Gel and 6-1/4 lbs. Gilsonite per sack, followed by 310 sacks 50-50 Pozmix with 2% Gel and 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack. Cement circulated to surface.

FOR: LAURENCE C. KELLY

18. I hereby certify that the foregoing is true and correct

President, Walsh Engr.

SIGNED

ORIGINAL SIGNED BY
EWELL N. WALSH

TITLE

& Production Corp.

DATE

8/31/81

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC

Sam