In Lieu of

## **UNITED STATES**

FORM APPROVED

Form 3160-5 DEPARTMENT OF (June 1990) BUREAU OF LAND			Budget Bureau No. 1004-0135 Expires: March 31, 1993		
	SUNDRY NOTICES ANI e this form for proposals to drill or to deepen or re  -" for such proposals	O REPORTS ON WELLS entry to a different reservoir. Use "APPLICATION FOR			
		DEGERMA	5. Lease Designation and Serial No. SF-077754		
		DECEIVED	6. If Indian, Allottee or Tribe Name N/A		
	SUBMIT IN	4 4 1000	7. If Unit or CA, Agreement Designation		
1.	Type of Well  ☐ Oil Well  ☐ Gas Well  ☐	DIST. 3	8. Well Name and No. Kelly Brothers#2		
2.	Name of Operator  Laurence C. Kelly		9. API Well No. 30-045-25161		
3.	Address and Telephone No. 7415 E. Main, Farmington, NM 87401 (5	05) 327-4892	10. Field and Pool, or Exploratory Area Blanco Pictured Cliffs		
4.	Location of Well (Footage, Sec., T., R., M., or S 1490' FSL & 1560' FEL, Sec. 8, T30N, R10	• • •	11. County or Parish, State San Juan, NM.		
	CHECK APPROPRIAT	TE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA		
	TYPE OF SUBMISSION	TYPE OF ACTION			
☐ Notice of Intent		☐ Abandonment☐ Recompletion	☐ Change of Plans ☐ New Construction		
⊠ Subsequent Report		☐ Plugging Back	☐ Non-Routine Fracturing		
☐ Final Abandonment		☑ Casing Repair ☐ Altering Casing ☐ Other <u>see below</u>	☐ Water Shut-Off ☐ Conversion to Injection ☐ Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and		

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well 13. is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Well production had fallen off drastically - suspected plugged tbg. Moved rig onto location on 1/18/99. Pulled tbg. - looked OK. TIH w/ retrievable bridge plug & packer & found casing leak between 131' - 162'. RU Cementer's Inc. & pumped 50 sx. of Class "B" cement w/ 3% CaCl2. Circulated cement out braden head. Shut braden head valve & squeeze cement, max squeeze pressure 1000#. Drilled out cement & pressure test casing to 1000# - held OK. Circulated hole clean. Latched onto retrievable 'bridge plug & TOH. Run 1-1/4" tbg. & land as before. Swab well to kick off. Release rig & return well to production on 1/22/99.

14.	I hereby certify that the foregoing is true and correct				
	Signed John C. Tho	ompson) Title	Agent/Engineer	— Dat AC	GPAPA FOR RECORD
	(This space for Federal or State office use)				
	Approved by	Title		Date _	FEB 1 9 1999
				<u>F#</u>	PRINCE TO A PRINCE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fix thous or fraudulent statements or representations as to any matter within its jurisdiction.