

NEW MEXICU ENEKGY, MINEKALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION
AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC MIL 87418
(606) 334-4178 FAX: (606) 334-4170
http://www.rd.state.nm.use/ocd/District MI/3distric.

This form is not to be used for reporting packer leakage tests in Southeast New Mexico



Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator_	Phillips Petr	coleum -0176	Lease Na	ame San J	uan 32-7 Unit	Well No_ ⁷⁹
ocation of	Well:Unit Letter_	JSec	7_Twp_311	<u>N_Rge_8₩</u>	API # 30-0 <u>45-2</u>	5207
	NAME OF RESERVOIR OR POOL			F PROD. or Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)
Upper Completion	Pictured Cliffs		gas		flowing	tubing
Lower Completion	Mesaverde	gas		flowing	tubing	
		PRE-	FLOW SHUT-I	N PRESSUR	E DATA	
Upper Completion	Hour, date shut-in		Length of time	shut-in	SI press. Psig	Stabilized? (Yes or No)
Lower Completion	Hour, date shut-in		Length of time	shut-in	SI press. Psig	Stabilized? (Yes or No)
			FLOW TI	EST NO. 1		
Commenceu at	(hour, date)*			Zone producing	(Upper or Lower):	<u> </u>
TIME (hour,date)	LAPSED TIME PRESSUI		SURE Lower Completion	PROD. ZONI TEMP.	Ĕ	REMARKS
<u></u>						
Production r	rate during test					
		BOPD bas	ed on	Bbls. ir	LHours	GravGOR
Gas:		M	CFPD; Tested t	hru (Orifice o	r Meter):	
-			-TEST SHUT-	IN PRESSUR	E DATA	·
Upper Completion	Hour, date shut-in		Length of time	· · · · · · · · · · · · · · · · · · ·	SI press psig	Stabilized? (Yes or No)
Lower Completion	Hour, date shut-in		Length of time		SI press. psig	Stabilized? (Yes or No)
			(Continue o	n reverse side		

32-7#79 PC/mV FLOW TEST NO. 2 Zone producing (Upper or Lower): Commenced at (hour, date) ** PRESSURE MU PROD. ZONE TIME LAPSED TIME REMARKS TEMP. SINCE ** Upper Completion **Lower Completion** (hour, deta) 16-2-01 40# 10-3 Production rate during test Oil: ______BOPD based on _____Bbls. in ____Hours. ____Grav. ____GOR ____ Gas: MCFPD: Tested thru (Orifice or Meter): Remarks: I hereby certify that the information herein contained is true and complete to the best of my knowledge. Operator Mexico Oil Conservation Division

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previly shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadwer pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beging of each flow-period, at fifteen-minute intervals during the first hour thereof, as hourly intervals thereafter, including one pressure measurement immediately prior to conclusion of each flow period. 7-day tests: immediately prior to the beginning of flow period, at least one time duting each flow period (at approximately the mic point) and immediately prior to the conclusion of each flow period. Other pressures be taken as desired, or may be requested on wells which have previously shown q tionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continue measured and recorded with recording pressure gauges the accuracy of which mus checked at least twice, once at the beginning and once at the end of each test, wi deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the rec ing gauge shall be required on the oil zone only, with deadweight pressures as required being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days: completion of the test. Tests shall be filed with the Aztec District Office of the New Mc Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Rev 10-01-78 with all deadweight pressures indicated thereon as well as the flow temperatures (gas zones only) and gravity and GOR (oil zones only).

