

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

below.)
AT SURFACE: 790' FNL - 1650' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) _____

SUBSEQUENT REPORT OF:

□
X
□
□
□
□
□
□

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-7-83 Killed well. Pulled and laid down 2-3/8" tubing.

4-8-83 Fraced Dakota perfs with 48,350 gal Mini Max 12-30
60,000# 20-40 sand 60,000# 20-40 sand
10,050# 10-20 sand 10,050# 10-20 sand
26 bbl. condensate 26 bbl. condensate
60 gal. Aquaflo 60 gal. Aquaflo
50# B-5 breaker & 23# B-11

4-12-83 Landed 170 jts. 1 1/4" O.D., 2.4#, V-55, 10 rd. EUE tubing
T.E. 5442.92' set at 5450' RKB.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

***See Instructions on Reverse Side**

MMOCG