

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

M.R. SCHALK

3. ADDRESS OF OPERATOR

P O BOX 25825/ALBUQUERQUE, NM 87125

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1670' FNL; 840' FWL; SEC. 15
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐


MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) SET PRODUCTION CASING ☐

SUBSEQUENT REPORT OF:



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/29/81

RAN 163 JTS. 5 1/2" 15.5 LB. PRODUCTION CASING, SET AT 6709'.
CEMENTED IN THREE STAGES:

1ST. - 205 SKS HALLI. LITE CLASS 'B' 50/50 POZ, 6% GEL, 2#
MED TUF PLUG P/SK W/7.7 GAL/SACK YEILD = 1.54 FT 3/
SACK & .8% FLUID LOSS ADDITIVE. FOLLOWED BY 100 SKS
CLASS 'B' NEAT.

2ND. - 280 SKS HALL. LITE CLASS 'B' 65/35 POZ, 6% GEL, 2# MED
TUF PLUG P/SK W/10.9 GAL/SACK YIELD 1.97 FT 3/SACK &
.8% FLUID LOSS ADDITIVE.

CONTINUED ON BACK

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

STEVE SCHALK

TITLE AGENT

DATE 1/4/82

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JAN 12 1982

*See Instructions on Reverse Side

NMOCC

FARMINGTON DISTRICT

BY

Sm

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

CONTINUED #17

3RD. - 285 SKS HALLI. LITE CLASS 'B'
65/35 POZ, 6% GEL, 2# TUF PLUG
P/SK W/10.9 GAL/SACK YIELD 1.97
FT 3/SACK 8.8% FLUID LOSS ADDITIVE.