

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Anador Resources, Inc.
3. ADDRESS OF OPERATOR
5700 S. Quebec Suite 320, Englewood, CO 80111
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL, 1980' FWL, Sec. 19, 30N, 15W
AT TOP PROD. INTERVAL: " " " "
AT TOTAL DEPTH: " " " "

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Set Casing

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐

X

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE
NM 42428
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
NONE
8. FARM OR LEASE NAME
Anador Federal
9. WELL NO.
1-19
10. FIELD OR WILDCAT NAME
Horseshoe Gallup
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 19, T20N, R15W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5340 G.L., 5352 D.F., 5353 K.B.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud at 7:00 p.m. 12-4-81.

Ran 6 jts. 8 5/8" 24# S.T.&C. casing to 268' K.B. in 12 1/2" hole. Cemented w/175sxs Class B w/3% c.c. Had full returns, cement circ. to surface. Ran 99 jts. 4 1/2" K-55 10.5# S.T.&C. casing in 7 7/8" hole to 4148' K.B. (T.D. is 4152'). DV tool at 3695' K.B. Ran 16 centralizers and 4 baskets. Cemented 1st stage w/20Bbls. Mud Flush, 150 sxs. 50-50 POZ w/2% Gel, #/sx Tuff Plug, .8% NFL-2 @ 10#/sx Gilsonite. B.P. w/1000 PSIG @ 3:30 p.m. 12-11-81. Opened DV tool @3:45 p.m. & cemented 2nd stage w/ 20Bbls. Mud Flush, 650 sxs. 65-35 POZ w/6% Gel, 2#/sx Tuff Plug & .8% NFL-2. Tailed in @/100 sxs. Class B. B.P. w/2000 PSIG @7:30 p.m. Float held, circ. 5 Bbls. Mud Flush to surface. Will find cement top w/Bond Log.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct


SIGNED _____ TITLE Chief Engineer DATE 12-21-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side



ACCEPTED FOR RECORD

JAN 4 1982
FARMINGTON DISTRICT