

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| | | |
|--------------|--|--|
| DISTRIBUTION | | |
| SANTA FE | | |
| FILE | | |
| U.S.G.S. | | |
| LAND OFFICE | | |
| OPERATOR | | |

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|--|---|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 7. Unit Agreement Name |
| 2. Name of Operator <u>ROY L. OWEN, dba THE OWEN DRILLING FUND</u> | 8. Farm or Lease Name <u>ThurLand</u> |
| 3. Address of Operator <u>W.M. GALLAWAY, 3005 Northridge, Ste T, Farmington NM 87401</u> | 9. Well No. <u>1</u> |
| 4. Location of Well UNIT LETTER <u>C</u> <u>700</u> FEET FROM THE <u>NORTH</u> LINE AND <u>1650</u> FEET FROM THE <u>WEST</u> LINE, SECTION <u>33</u> TOWNSHIP <u>30N</u> RANGE <u>15W</u> NMPM. | 10. Field and Pool, or Wildcat <u>MEADOWS GALLUP</u> |
| 15. Elevation (Show whether DF, RT, GR, etc.) <u>5196 RT 5123 GR</u> | 12. County <u>SAN JUAN</u> |

16. Check appropriate box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO

RECEIVED
JUN 9 1992
OIL CON. DIV.
DIST. 3

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ REMEDIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐ CHANGE PLANS ☒ CASING TEST AND CEMENT JOB ☐
OTHER ☐ SUBSEQUENT REPORT OF:

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

1. SET CEMENT RETAINER AT 1800', Pump down 2 3/8" tubing, ESTABLISH RATE AT 2 bbls. per min., then pump 119 SACKS OF CEMENT, displace with 7 BARRELS of fluid, string out retainer, come out of hole
2. PERFORATE 4-1/2" casing at 1400' spot 40 sack plug inside and outside from 1475' to 1325'
3. PERFORATE 4-1/2" casing 50' below surface at 264', BREAK CIRCULATION and spot a 50 sack plug inside and outside of 4-1/2" casing
4. ERECT dry hole marker with cement
5. RESTORE LOCATION to a safe and clean condition

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W.M. Gallaway TITLE Agent DATE 6-19-92

APPROVED BY Chuck Thulman TITLE _____ DATE 6-19-92

CONDITIONS OF APPROVAL, IF ANY: