

NEW MEXICO OIL CONSERVATION COMMISSION

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Roy L. Owen, dba The Owen Drilling Fund	8. Farm or Lease Name ThurLand
3. Address of Operator Wm GALLAWAY, 3005 Northridge, Ste T, Farmington NM 87401	9. Well No. 1
4. Location of Well UNIT LETTER C, 700 FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 33 TOWNSHIP 30N RANGE 15W NMPM.	10. Field and Pool, or Wildcat MEADOWS GALLUP
15. Elevation (Show whether DF, RT, GR, etc.) 5196 RT 5183 GR	12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input checked="" type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

1. SET CEMENT RETAINER AT 1800', Pump down 2 3/8" tubing, ESTABLISH RATE AT 2 bbls. per min., then pump 119 SACKS OF CEMENT, displace with 7 barrels of fluid, sting out retainer, come out of hole
2. PERFORATE 4-1/2" casing at 1400' spot 40 sack plug inside and outside from 1475' to 1325'
3. PERFORATE 4-1/2" casing 50' below surface at 264', BREAK CIRCULATION and spot a 50 sack plug inside and outside of 4-1/2" casing
4. ERECT dry hole marker with cement
5. RESTORE LOCATION to a safe and clean condition

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W.M. GALLAWAY TITLE AGENT DATE 6-19-92

Original Signed by CHARLES GROLSON

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE JUN 19 1992

CONDITIONS OF APPROVAL, IF ANY: