Form 9-331 Dà

5 MMS, Fmn 1 Ladd, DE

1 File

14. API NO.

Form Approved. Budget Bureau No. 42-R1424

ic. 1973	UNITED STATES							
	DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY							
SUNDR'	Y NOTICES	AND	REPORTS	ON	WELLS			

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE NM 90867-A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME				
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME				
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Butte				
1. oil gas well XX other	9. WELL NO. 1E				
2. NAME OF OPERATOR Ladd Petroleum Corp.	10. FIELD OR WILDCAT NAME Basin Dakota				
3. ADDRESS OF OPERATOR P O Box 208, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA				
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 600' FSL - 612' FWL AT SURFACE: AT TOP PROD. INTERVAL:	Sec 18 T30N R13W 12. COUNTY OR PARISH 13. STATE San Juan NM				

2.	NAME OF OPERATOR Ladd Petroleum Corp.
3.	ADDRESS OF OPERATOR P O Box 208, Farmington, NM 87401
4.	LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 600' FSL - 612' FWL AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

15. ELEVATIONS (SHOW DF, KDB, AND WD) 5803' GL; 5815' RKB

change on Form 9-330

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)

SUBSEQUENT REPORT OF: JUL 20 1982 (NOTE: Report results of multig U. S. DECLOCION DURVEY FARMINGTON, N. M. Spud & Surface csg.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MI & RU Arapahoe #10. Spudded 12½" hole at 1:00 p.m., 7-17-82. 7-18-82 Ran 6 jts. 8-5/8" O.D., 24#, J-55, 8R, ST&C casing. T.E. 251' set at 263' RKB. Woodco cemented surface with 145 sx class B (171 cu.ft.) P.O.B. at 6:30 p.m. 7-17-82. Good cement to surface.

			•	• • • •
a C. L. Value Mague and Type			Set @ _	Ft.
Subsurface Safety Valve; Mario, and Type				
Subsurface Safety Valve: Manue and Type 18. I hereby certify that the foregoing is true and the	correct Agent	DATE	7-19-82	· · · · · · · · · · · · · · · · · · ·
SIGNED THOMAS DUGANTI				FPTER FOR NECORD
(This sq	pace for Federal or State office use)		1.144.00	
APPROVED BY CONDITIONS OF APPROVAL, IF ANY	TITLE	_ DATE		JUL 29 1982
	NAMA			

NMULT:

FARMINGTS : EBTRICT