

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Northwest Pipeline Corporation
3. ADDRESS OF OPERATOR
P.O. Box 90, Farmington, N.M. 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1695 FSL & 660 FWL NW/SW
AT TOP PROD. INTERVAL: 1695 FSL & 660 FWL
AT TOTAL DEPTH: 1695 FSL & 660 FWL
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

Spud & Drlg Operations

RECEIVED

NOV 04 1982

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
SF 078996
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 32-7 Unit
8. FARM OR LEASE NAME
San Juan 32-7 Unit
9. WELL NO.
#80
10. FIELD OR WILDCAT NAME
South Los Pinos Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 3, T31N, R7W
12. COUNTY OR PARISH 13. STATE
San Juan N.M.
14. API NO.
30-045-25391
15. ELEVATIONS (SHOW DF, KDS, AND WD)
6754' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-17-82 MOL & RU. Spudded at 1300 hrs 10-17-82. Ran 3 jts 8-5/8", 24#, K-55, ST&C csg & set at 138' KB. Woodco cmt'ed w/ 90 sx (107 cu.ft) C1 "B" w/ 1/4# Flocele/sx & 3% CaCl₂. Displaced cmt w/ 7-1/2 bbls & down at 1830 hrs 10-17-82. Circ out 7-1/2 bbls cmt. WOC.

10-18-82 Pressure tested csg to 600# - held OK. Drlg ahead.

10-19-82 Drlg ahead

10-20-82 Drlg ahead

10-21-82 Drlg ahead

10-22-82 Drlg ahead

10-23-82 TD'ed hole at 3830'.

10-24-82 Gearhart ran IES & CNL/CDL/GR logs. Ran 124 jts 2-7/8", 6.4#, J-55 & NU 10rd csg & set at 3325' KB. Howco cmt'ed w/ 75 sx (183 cu.ft) C1 "B"

10-25-82 65/35 poz w/ 12% gel & 12-1/2# fine gilsonite/sx. Tailed w/ 150 sx

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

CONTINUED ON REVERSE SIDE

18. I hereby certify that the foregoing is true and correct

SIGNED Donna J. Brace TITLE Production Clerk DATE October 26, 1982
Donna J. Brace

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY

B
djb/ 1

NOV 5 1982

*See Instructions on Reverse Side

NMOCG

FARMINGTON
BY Smn

17 continued 121

10-24-82 & (297 cu.ft) C1 "B" w/ 6% gel & 12-1/2# gils/sx. Displaced

10-25-82 2 - 3-1/16" balls and Omega Latch Down plug w/ 1 bbl of acetic acid and 21 bbls wtr. Bumped plug & tested csg to 4000 psi - OK. Plug down at 0845 hrs 10-25-82. Wilson ran temp survey and found top of cmt at 1700, PBTD at 3815'. (Ojo Alamo at 2466'). Rig released at 0900 hrs 10-25-82.

NOW WAITING ON COMPLETION.