

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

Do not use this form for proposals to drill or to deepen a well in a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

070 FARMINGTON, NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Attention:

Amoco Production Company

Patty Haeefe

3. Address and Telephone No.

P.O. Box 800, Denver, CO 80201

(303) 830-4988

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1120' FSL 950' FEL Sec. 2 T 30N R 11W Unit P

5. Lease Designation and Serial No.

SF-078144

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Blanco Com 1-1A

9. API Well No.

3004525441

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Bradenhead

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Amoco Production Company has completed a bradenhead repair per the following:

MIRUSU 10/17/95. SICP 330 psi. Bradenhead pressure 30 psi. Fish with overshot. Set RBP at 4592 ft. Test to 76 ft. Circ dye to surface. Perforated at 720 ft with 2 JSPF, 2 total shots, 310" diameter, 4" gun size, 180 deg phasing. 12.5 gms - Cement 13-720 ft with 75 sx Class B cement and 23 sx Class B neat. Circulate to surface. Bradenhead pressure 0 psi. Tag at 540 ft. Drill out 186 to 726 ft. Pressure test to 650 psi for 10 min, ok. Tag sand at 4582 ft, uload 165 bbls and 10' of sand with N2. Cleanout 726-540 ft. Slickline tag at 6875 ft. TIH with sand bailer 6875 ft. Tag at 6905 ft, bail to 6916 ft. RDMOSU 10/27/95.

RIH w/ 2 3/8 - Landed tbg @ 6892' w/ production packer @ 4874'
Mesaverde tbg. Landed @ 4760' - 2 3/8 TH.

14. I hereby certify that the foregoing is true and correct

Signed

Patty Haeefe

Title

Staff Assistant

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

NOV 28 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false statement or representations as to any matter within its jurisdiction.

AMOCO

FARMINGTON DISTRICT OFFICE
BY [Signature]

Reverse Side