

5 BLM, Fmn 1 File
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1850' FSL - 1650' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☒

RECEIVED
JAN 19 1984
FARMINGTON RESOURCE AREA

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

XX Spud & Surface casing

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-11-84

Moved in and rigged up Four Corners Drilling Co. Rig #4.
Spudded 12-1/4" hole at 4:00 p.m. 1-10-84. Drilled to 215' RKB.
Ran 5 jts. 9-5/8" O.D., 43.5#, 8 Rd, LT&C casing. T.E. 195'
set at 207' RKB. Cemented with 115 sx class "B" plus 2% CaCl.
(136 cf). P.O.B. at 9:45 p.m. 1-10-84. (Circulated
approximately 2 1/2 bbls. cement.)

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft. IV.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs

TITLE Geologist

DATE 1-11-84

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

FARMINGTON RESOURCE AREA

BY smm