

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>	
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Carson Gas Com	
9. Well No. 1E	
10. Field and Pool, or Wildcat Basin Dakota	
12. County San Juan	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER-	
2. Name of Operator Amoco Production Company	
3. Address of Operator 501 Airport Dr., Farmington, NM 87401	
4. Location of Well UNIT LETTER <u>F</u> <u>1470</u> FEET FROM THE <u>North</u> LINE AND <u>1460</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>30N</u> RANGE <u>12W</u> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.) 5445' GL	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <u>Completion</u> <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Completion operations commenced on 1-25-83. Total depth of the well is 6254' and plug-back depth is 6200'. Perforated intervals 6152-6130', 6130-6110', 6076-6070', and 6054-6046' with 2 jspf, a total of 112 holes at .38". Fraced interval with 114,000 gallons of 70 quality nitrogen foam containing 2% KCL, 1 gal/1000 surfactant and 192,000# 20/40 sand. Landed 2-3/8" at 6149' and released the rig on 1-29-83.

OIL CON. DIV.  
DIST. 3

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed By B.F. Nelson TITLE Admin. Supvr. DATE 3-2-83

APPROVED BY Original Signed By TITLE DEF DATE MAR 3

CONDITIONS OF APPROVAL, IF ANY: