

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
501 Airport Drive, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1790' FNL x 1650' FWL
AT 10F PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
NM-0546
6. INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Bell Federal Gas Com "B"
9. WELL NO.
1F
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SE/NW, Section 11, T30N, R.
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
30-045-25643
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5879' GL

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐
- (other) Spud and set casing

SUBSEQUENT REPORT OF:

RECEIVED

JUN 2 1983

(NOTE: Report results of multiple completion or zone change on Form 9-332)

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to the work.)

Spudded a 12-1/4" hole on 4-13-83 and drilled to 330'. Landed 8-5/8", 24#, R-5 casing at 329' and cemented with 360 cu. ft. Class B cement with 2% CaCl₂. Circulated good cement to surface. Drilled a 7-7/8" hole and reached a TD of 6680' 4-25-83. Ran 4-1/2", 10.5#, J-55 casing and landed it at 6680'. Cemented first stage with 693 cu. ft. Class B 50:50 POZ cement. Tailed in with 118 cu. ft. Class B neat cement. Set DV tool at 4828'. Cemented second stage with 2758 cu. ft. Class B 65:35 POZ cement and tailed in with 118 cu. ft. neat cement. Circulate cement to surface on both stages. Released rig on 4-29-83.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Admin. Supvr. DATE 5/31/83

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

JUN 0 1983

NMDC